

Mercedes-Benz

AP00.20-U-1208IH SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

Model	Year	2012
USA		

Model 221



Customer:			Repair order nu	mber:		
Tire Rotation (non-staggered width wheel setup only)	A 5,000-mile recommende likely necessitate tire rotati each 10,000-mile maintena 10,000-mile maintenance s	on at least once in between ance service and at every	Tires rotated	YES _		NO
Note: For any co	ondition found while performirm the repair using a separate	ng the checks or inspections e repair order.	s included in this I	maintenance	sheet,	determine
Current mileage read	ding:	_ Oi	grade/viscosity:			
Additional notes:						
Service work to be poservice advisor:	erformed as advised by	Completion date:	Confirm work ha below:	s been perfor	med by	y signing

Required Service Work miles (thousands) Performed years (check if performed)	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
Reset maintenance service indicator in instrument cluster		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0042SX
□ Engine - oil and filter change engine 157 engine 272 engine 275.982 engine 275.953 engine 278		• • • • •	• • • • •	• • • • •	• • • • •	• • • • •	• • • •	• • • • •	• • • • •		• • • • •		• • • • •			• • • • •		AP18.00-P-0101EWG AP18.00-P-0101PIT AP18.00-P-0101SZB AP18.00-P-0101SZA AP18.00-P-0101EL
engine 642		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101EWO
Check catch, safety catch and hinges on engine hood for proper operation		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP88.40-P-8851SX
☐ Fill up with DEF engine 642 with CODE U42 (BlueTEC diesel exhaust treatment (SCR)) i fill, subject to a separate invoice		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP14.40-P-1410BT
Check water drain in air/water duct for obstructions; clean if soiled		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP83.10-P-8339M
Check condition of poly-V-belt except S400 HYBRID engine 157, 278 engine 275			•		•		:		•		:		•		•			AP13.22-P-1352SX AP13.22-P-1352SZ
engine 642			•		•		•		•		•		•		•			AP13.22-P-1352SXI
Replace fuel filter engine 642			•		•		•		•		•		•		•			AP47.20-P-0780SXI
Replace brake fluid			•		•		•		•		•		•		•			AP42.00-P-4280SX
Replace combination filter			•		•		•		•		•		•		•			AP83.00-P-8384SX
☐ Check thickness of brake pads, front and rear		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4253A
Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.15-P-4061A
Leakage - major components - check underbody and engine compartment for chafe marks, line routing, damaged components			•		•		•		•		•		•		•			AP00.20-P-0053SX
☐ Check DEF lines and components for leaks and damage engine 642 with CODE U42 (BlueTEC diesel exhaust treatment (SCR))			•		•		•		•		•		•		•			AP00.20-P-0053SX
☐ Visually inspect condition of front axle ball joints, rubber boots			•		•		•		•		•		•		•			AP33.20-P-3353SX
☐ Visually inspect condition of driveshaft flexible discs			•		•		•		•		•		•		•			AP41.10-P-4152SX
Visually inspect condition of steering mechanical components, rubber boots			•		•		•		•		•		•		•			AP46.00-P-4653SX
Coolant - check fluid level and correct if necessary engine 157, 272, 278; engine 275 main and low temperature circuit (main circuit if not to be replaced (every 30k miles/3 yrs)) refer to AH20.00-P-1142-01V observe correct coolant composition		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Coolant - check fluid level and correct if necessary engine 642 i refer to AH20.00-P-1142-01SXI observe correct coolant composition		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Brake system - check fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	Ш	AP42.10-P-4210SX

Required Service Work miles (thousands) Performed years (check if performed)	2	10 1	20 2	30	40 4	50 5	60 6	70 7	80 8	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
Power steering - check fluid level and correct if necessary i the fluid level must always be on the maximum mark, corresponding to the oil temperature		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP46.00-P-4611SX
Windshield washer system - check fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8210SX
☐ Active Body Control - check fluid level and correct if necessary with Code 487 (Active Body Control (ABC))		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP32.50-P-3213SX
☐ Parking brake (function test only)			•		•		•		•		•		•		•			AP42.00-P-4290BA
Reset maintenance service indicator in instrument cluster irreminder - if not yet performed		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0042SX
Required Additional Work miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
Performed years (check if performed)	2	1	2	3	4	5	6	7	8	9	100	11	12	13	14	150	Not OK ↓	
Replace air filter except engine 275 engine 157, 278 engine 272					•				•				•					AP09.10-P-0980AB AP09.10-P-0980SX
engine 642 with side mounted air filter elements					•				•				•					AP09.10-P-0980SXI
engine 642 with top mounted air filter elements					•				•				•					AP09.10-P-0980GZB
Replace air filter engine 275							•						•					AP09.10-P-0980SZ
□ Automatic transmission - oil and filter change except engine 278, 642 engine 157 with NAG2-V Sport and wet start-up clutch, engine 272 with NAG2 - S400 HYBRID (transmission 722.9)		·			•				•				•					AP27.00-P-2702W
engine 275 with NAG1 (transmission 722.6)					•				•				•					AP27.00-P-2702SX
Automatic transmission - oil and filter change engine 278, 642 with NAG2-FE+ (transmission 722.9)								•							•			AP27.00-P-2702W
Replace V-belts S400 HYBRID							•						•					AP13.20-P-1380A
Replace spark plugs except engine 642 engine 157, 272, 278													_					AP15.10-P-1580SX
engine 275							_						_					AP15.10-P-1580SZ
Replace fuel filter							_						_			_		AP47.20-P-0780SX
engine 157, 272, 275, 278				_						_						_		AP20.00-P-2080SZ
Replace coolant engine 275 main circuit observe correct coolant composition				•			•			•			•			•		AF20.00-F-200052
Replace coolant except engine 275 main circuit engine 157, 272, 278, 642																		AP20 00 P 2000SV
																•		AP20.00-P-2080SX
engine 275 low temperature circuit	_													4-		•		AP20.00-P-2080SZ
Recommended Service miles (thousands) Work Performed years (check if performed)	2	10	20	30	40	50 5	60	70	80	90	100	110	120	130	140 14	150 15	Not OK	
☐ Main/starter battery - Check fluid level and correct if necessary with lead acid battery		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.10-P-5410SX

Recommended Service miles (thousands) Work	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
Performed years (check if performed)		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK ↓	
☐ Horn - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Warning/indicator lamps - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5451SX
☐ Illumination and interior lighting - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5453SX
☐ Exterior lighting, high beam flasher, hazard warning flasher, turn signals - Electrical system check		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.10-P-8252EW
☐ Check trunk/cargo area lighting		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check and correct headlamp setting			•		•		•		•		•		•		•			AP82.10-P-8260SX
☐ Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midtronics test report print out here		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.10-U-5453A
☐ Check seat belts and buckles for signs of external damage and proper function			•		•		•		•		•		•		•			AP91.40-P-9150SX
☐ Check windshield washer and headlamp cleaning system		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.30-P-8252SX
☐ Check, clean, and lubricate tilt/sliding roof mechanism except CODE 413 (panoramic glass roof with top sliding roof)			•		•		•		•		•		•		•			AP77.20-P-7731SX
☐ Check, clean, and lubricate panoramic roof mechanism with CODE 413 (panoramic glass roof with top sliding roof)			•		•		•		•		•		•		•			AP77.20-P-7732SX
☐ Check bodywork for paintwork damage			•		•		•		•		•		•		•			AP98.00-P-9850SX
☐ Night View Assist camera - clean windshield behind the camera cover with CODE 610 (Night View Assist)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5431SX
☐ Tire rotation where applicable		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Inspect tires for damage, measure thread depth and enter table at the end of the service sheet		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4051Z
☐ Check TIREFIT tire sealant expiration date where applicable		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4054R
Activate Tire Pressure Monitoring System irefer to vehicle Operator's Manual		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Visually check brake system components, lines, hoses, calipers		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
$\hfill\Box$ Check thickness of brake pads and discs, front and rear wheels removed																		
pads 		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4253A
discs		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4258SX
☐ Check chassis and load-bearing body components for damage and corrosion			•		•		•		•		•		•		•			AP00.20-P-0090SX
Replace wiper blades	<u> </u>	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
High Mileage Required Service Work at 1											_	20,0)00 i	mile	s or	2 ye	ars	
i Plus any applicable additional work li☑ Performed	ste	d at	tne	e er	ıa c	ot tr	1e s	erv	ICE	sne	eet						Not OK	
(check if performed)																	Ψ.	
☐ Reset maintenance service indicator in ir	stru	ıme	ent d	clus	ter													AP00.20-P-0042SX
☐ Engine - oil and filter change engine 157 engine 272																		AP18.00-P-0101EWG AP18.00-P-0101PIT
engine 272 engine 275.982																		AP18.00-P-0101SZB

engine 275.953		AP18.00-P-0101SZA
engine 278		AP18.00-P-0101EL
engine 642		AP18.00-P-0101EWO
Check catch, safety catch and hinges on engine hood for proper operation		AP88.40-P-8851SX
Fill up with DEF engine 642 with CODE U42 (BlueTEC diesel exhaust treatment (SCR))		AP14.40-P-1410BT
i fill, subject to a separate invoice		
☐ Check water drain in air/water duct for obstructions; clean if soiled		AP83.10-P-8339M
Check condition of poly-V-belt except S400 HYBRID		
engine 157, 278		AP13.22-P-1352SX
engine 275		AP13.22-P-1352SZ
engine 642		AP13.22-P-1352SXI
Replace fuel filter engine 642		AP47.20-P-0780SXI
Replace brake fluid		AP42.00-P-4280SX
Replace combination filter		AP83.00-P-8384SX
☐ Check thickness of brake pads, front and rear		AP42.10-P-4253A
Correct tire inflation pressure including spare (where applicable) and enter in the table at the end of the service sheet		AP40.15-P-4061A
Leakage - major components - check underbody and engine compartment for chafe marks, line routing, damaged components		AP00.20-P-0053SX
Check DEF lines and components for leaks and damage engine 642 with CODE U42 (BlueTEC diesel exhaust treatment (SCR))		AP00.20-P-0053SX
☐ Visually inspect condition of front axle ball joints, rubber boots		AP33.20-P-3353SX
□ Visually inspect condition of driveshaft flexible discs		AP41.10-P-4152SX
Usually inspect condition of steering mechanical components, rubber boots		AP46.00-P-4653SX
Coolant - check fluid level and correct if necessary engine 157, 272, 278; engine 275 main and low temperature circuit (main circuit if not to be replaced (every 30k miles/3 yrs)) i refer to AH20.00-P-1142-01V		
i observe correct coolant composition		
Coolant - check fluid level and correct if necessary engine 642 i refer to AH20.00-P-1142-01SXI		
i observe correct coolant composition		
☐ Brake system - check fluid level and correct if necessary		AP42.10-P-4210SX
Power steering - check fluid level and correct if necessary i the fluid level must always be on the maximum mark, corresponding to the oil temperature		AP46.00-P-4611SX
☐ Windshield washer system - check fluid level and correct if necessary		AP82.35-P-8210SX
Active Body Control - check fluid level and correct if necessary with Code 487 (Active Body Control (ABC))		AP32.50-P-3213SX
☐ Parking brake (function test only)		AP42.00-P-4290BA
Reset maintenance service indicator in instrument cluster		AP00.20-P-0042SX
i reminder - if not yet performed		
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles	or 2 yea	ırs
i Plus any applicable additional work listed at the end of the service sheet		
☑ Performed	Not OK	(
(check if performed)	<u> </u>	
Main/starter battery - Check fluid level and correct if necessary with lead acid battery		AP54.10-P-5410SX
☐ Horn - Electrical system check		

☐ Warning/indicator lamps - Electrical system check		AP54.30-P-5451SX
☐ Illumination and interior lighting - Electrical system check		AP54.30-P-5453SX
☐ Exterior lighting, high beam flasher, hazard warning flasher, turn signals - Electrical system check		AP82.10-P-8252EW
☐ Check trunk/cargo area lighting		
☐ Check and correct headlamp setting		AP82.10-P-8260SX
☐ Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midtronics test report print out here		AP54.10-U-5453A
\square Check seat belts and buckles for signs of external damage and proper function		AP91.40-P-9150SX
☐ Check windshield washer and headlamp cleaning system		AP82.30-P-8252SX
☐ Check, clean, and lubricate tilt/sliding roof mechanism except CODE 413 (panoramic glass roof with top sliding roof)		AP77.20-P-7731SX
☐ Check, clean, and lubricate panoramic roof mechanism with CODE 413 (panoramic glass roof with top sliding roof)		AP77.20-P-7732SX
☐ Check bodywork for paintwork damage		AP98.00-P-9850SX
☐ Night View Assist camera - clean windshield behind the camera cover with CODE 610 (Night View Assist)		AP54.30-P-5431SX
☐ Tire rotation where applicable		
\square Inspect tires for damage, measure thread depth and enter table at the end of the service sheet		AP40.10-P-4051Z
☐ Check TIREFIT tire sealant expiration date where applicable		AP40.10-P-4054R
☐ Activate Tire Pressure Monitoring System ☐ refer to vehicle Operator's Manual		
☐ Visually check brake system components, lines, hoses, calipers		
☐ Check thickness of brake pads and discs, front and rear wheels removed		
pads		AP42.10-P-4253A
discs		AP42.10-P-4258SX
Check chassis and load-bearing body components for damage and corrosion		AP00.20-P-0090SX
Replace wiper blades		
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2 yo	ears	
i Plus any applicable additional work listed at the end of the service sheet	Not Ok	r
i Plus any applicable additional work listed at the end of the service sheet ⊠ Performed	Not OF	(
i Plus any applicable additional work listed at the end of the service sheet ⊠ Performed (check if performed)	Not Or ↓	AP00.20-P-0042SX
☐ Plus any applicable additional work listed at the end of the service sheet ☐ Performed (check if performed) ☐ Reset maintenance service indicator in instrument cluster		
i Plus any applicable additional work listed at the end of the service sheet ⊠ Performed (check if performed)		
Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster □ Engine - oil and filter change		AP00.20-P-0042SX
Plus any applicable additional work listed at the end of the service sheet ☑ Performed (check if performed) ☐ Reset maintenance service indicator in instrument cluster ☐ Engine - oil and filter change engine 157		AP00.20-P-0042SX AP18.00-P-0101EWG
Plus any applicable additional work listed at the end of the service sheet ▶ Performed (check if performed) □ Reset maintenance service indicator in instrument cluster □ Engine - oil and filter change engine 157 engine 272		AP00.20-P-0042SX AP18.00-P-0101EWG AP18.00-P-0101PIT
Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) □ Reset maintenance service indicator in instrument cluster □ Engine - oil and filter change engine 157 engine 272 engine 275.982		AP00.20-P-0042SX AP18.00-P-0101EWG AP18.00-P-0101PIT AP18.00-P-0101SZB
 Plus any applicable additional work listed at the end of the service sheet ☑ Performed (check if performed) ☐ Reset maintenance service indicator in instrument cluster ☐ Engine - oil and filter change engine 157 engine 272 engine 275.982 engine 275.953 	•	AP00.20-P-0042SX AP18.00-P-0101EWG AP18.00-P-0101PIT AP18.00-P-0101SZB AP18.00-P-0101SZA
Plus any applicable additional work listed at the end of the service sheet		AP00.20-P-0042SX AP18.00-P-0101EWG AP18.00-P-0101PIT AP18.00-P-0101SZB AP18.00-P-0101SZA AP18.00-P-0101EL
Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster Engine - oil and filter change engine 157 engine 272 engine 275.982 engine 275.953 engine 278 engine 642 Check catch, safety catch and hinges on engine hood for proper operation Fill up with DEF engine 642 with CODE U42 (BlueTEC diesel exhaust treatment (SCR))	•	AP00.20-P-0042SX AP18.00-P-0101EWG AP18.00-P-0101PIT AP18.00-P-0101SZB AP18.00-P-0101SZA AP18.00-P-0101EL AP18.00-P-0101EWO
I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster □ Engine - oil and filter change engine 157 engine 272 engine 275.982 engine 275.982 engine 275.953 engine 278 engine 642 □ Check catch, safety catch and hinges on engine hood for proper operation □ Fill up with DEF engine 642 with CODE U42 (BlueTEC diesel exhaust treatment (SCR)) I fill, subject to a separate invoice	•	AP00.20-P-0042SX AP18.00-P-0101EWG AP18.00-P-0101PIT AP18.00-P-0101SZB AP18.00-P-0101SZA AP18.00-P-0101EL AP18.00-P-0101EWO AP88.40-P-8851SX
Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Reset maintenance service indicator in instrument cluster Engine - oil and filter change engine 157 engine 272 engine 275.982 engine 275.953 engine 278 engine 642 Check catch, safety catch and hinges on engine hood for proper operation Fill up with DEF engine 642 with CODE U42 (BlueTEC diesel exhaust treatment (SCR))	•	AP00.20-P-0042SX AP18.00-P-0101EWG AP18.00-P-0101PIT AP18.00-P-0101SZB AP18.00-P-0101SZA AP18.00-P-0101EL AP18.00-P-0101EWO AP88.40-P-8851SX AP14.40-P-1410BT

Coolant - check fluid level and correct if necessary engine 157, 272, 278; engine 275 main and low temperature circuit (main circuit if not to b (every 30k miles/3 yrs))	e replaced	
i refer to AH20.00-P-1142-01V i observe correct coolant composition		
Coolant - check fluid level and correct if necessary engine 642		
i refer to AH20.00-P-1142-01SXI		
i observe correct coolant composition		AP42.10-P-4210SX
☐ Brake system - check fluid level and correct if necessary		AP46.00-P-4611SX
☐ Power steering - check fluid level and correct if necessary ☐ the fluid level must always be on the maximum mark, corresponding to the oil temperate	_	AP46.00-P-46115X
		AP82.35-P-8210SX
☐ Windshield washer system - check fluid level and correct if necessary ☐ Active Body Control - check fluid level and correct if necessary with Code 487 (Active Body Control (ABC))		AP32.50-P-3213SX
Reset maintenance service indicator in instrument cluster i reminder - if not yet performed		AP00.20-P-0042SX
High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,	,000 miles or 2 yea	ars
Plus any applicable additional work listed at the end of the service sheet		
☑ Performed	Not OI	∢
(check if performed)	<u> </u>	
Main/starter battery - Check fluid level and correct if necessary with lead acid battery		AP54.10-P-5410SX
☐ Horn - Electrical system check		
☐ Warning/indicator lamps - Electrical system check		AP54.30-P-5451SX
☐ Illumination and interior lighting - Electrical system check		AP54.30-P-5453SX
Exterior lighting, high beam flasher, hazard warning flasher, turn signals - Electrical system	n check	AP82.10-P-8252EW
☐ Check trunk/cargo area lighting		
Battery (Main/starter/auxiliary) check condition using Midtronics battery tester. Attach Midt report print out here	tronics test	AP54.10-U-5453A
☐ Check windshield washer and headlamp cleaning system		AP82.30-P-8252SX
□ Night View Assist camera - clean windshield behind the camera cover with CODE 610 (Night View Assist)		AP54.30-P-5431SX
☐ Tire rotation where applicable		
\square Inspect tires for damage, measure thread depth and enter table at the end of the service s	sheet	AP40.10-P-4051Z
Check TIREFIT tire sealant expiration date where applicable		AP40.10-P-4054R
☐ Activate Tire Pressure Monitoring System ☐ refer to vehicle Operator's Manual		
☐ Visually check brake system components, lines, hoses, calipers		
Check thickness of brake pads and discs, front and rear wheels removed		
pads		AP42.10-P-4253A
discs		AP42.10-P-4258SX
Replace wiper blades		
High Mileage Additional Work Performed (check if performed)		
Replace air filter		
except engine 275		
engine 157, 278 If more than 40,000 mi or 4 years since last replace engine 272 If more than 40,000 mi or 4 years since last replace		AP09.10-P-0980AB AP09.10-P-0980SX
engine 642 with side mounted air filter elements If more than 40,000 mi or 4 years since last replace		AP09.10-P-0980SXI

engine 642 with top mounted air filter elements	If more than 40,000 mi or 4 years since last replacement	AP09.10-P-0980GZB
Replace air filter engine 275	If more than 60,000 mi or 6 years since last replacement	AP09.10-P-0980SZ
Automatic transmission - oil and filter change except engine 278, 642		
engine 157 with NAG2-V Sport and wet start-up clutch, engine 272 with NAG2 - S400 HYBRID (transmission 722.9)	If more than 40,000 mi or 4 years since last replacement	AP27.00-P-2702W
engine 275 with NAG1 (transmission 722.6)	If more than 40,000 mi or 4 years since last replacement	AP27.00-P-2702SX
☐ Automatic transmission - oil and filter change engine 278, 642 with NAG2-FE+ (transmission 722.9)	If more than 70,000 mi or 7 years since last replacement	AP27.00-P-2702W
Replace V-belts S400 HYBRID	If more than 60,000 mi or 6 years since last replacement	AP13.20-P-1380A
Replace spark plugs except engine 642		
engine 157, 272, 278	If more than 60,000 mi or 6 years since last replacement	AP15.10-P-1580SX
engine 275	If more than 60,000 mi or 6 years since last replacement	AP15.10-P-1580SZ
Replace fuel filter engine 157, 272, 275, 278	If more than 150,000 mi or 15 years since last replacement	AP47.20-P-0780SX
Replace coolant engine 275 main circuit observe correct coolant composition	If more than 30,000 mi or 3 years since last replacement	AP20.00-P-2080SZ
Replace coolant except engine 275 main circuit observe correct coolant composition		
engine 157, 272, 278, 642	If more than 150,000 mi or 15 years since last replacement	AP20.00-P-2080SX
engine 275 low temperature circuit	If more than 150,000 mi or 15 years since last replacement	AP20.00-P-2080SZ

Tire infl	Tire inflation pressure (bar/psi)										
LF	RF	LR	RR	Spare							

Tire thre	Tire thread depth (mm)											
	LF	RF	LR	RR								
outside												
center												
inside												