

Mercedes-Benz

AP00.20-U-1208IAC SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

Model 221

AMG models and \$600

Passenger cars Model Year 2007





Customer:		Repair order numb	per:	
First visit	at 1,000 - 3,000 miles	Performed	YES	NO
Tire Rotation (non staggered width wheel setup only)	Performed in accordance with the tire manufacturer's recommended intervals	Tires rotated	YES	NO
Tire Inspection (staggered and non- staggered width wheel setup)	Inspect tires for damage and correct tire inflation pressure	Tires inspected	YES	NO
Current mileage reading: Additional notes:			r:	
Service work to be performed service advisor:	as advised by Completion date:	Confirm worl below:	k has been perform	ed by signing

i

US Service 4 through US Service 20 apply to "Additional work" items only.

Vehicle determines need for US Service 3 (Engine oil and filter change) as well as US Service 1 or US Service 2.

Perform each service as described.

US Service		first at 10,000 mi or 1 year;	after first every 20,000 mi or 2 years	
1	US Service	first at 20,000 mi or 2 years;	after first every 20,000 mi or 2 years	
1	2 ↓		Not OK ↓	
		Interior - Required		
	0	Reset service indicator in instrument cluster		AP00.20-P-0042SX
	0	Check parking brake (function test only)		AP42.00-P-4290BA
		Interior - Recommended		
	0	Night View Assist camera - clean windshield behind the camera cover CODE 610 (Night View Assist)		AP54.30-P-5431SX
		Function test		
	0	Horn		
	0	Warning/indicator lamps		AP54.30-P-5451SX
	0	Illumination and interior lighting		AP54.30-P-5453SX
	0	Windshield wipers, windshield washer system, headlamp cleaning system		AP82.30-P-8252SX
	0	Check seat belts and buckles for signs of external damage and proper function		AP91.40-P-9150SX
		Wheels, brakes - Required		
1	1		_	
	0	Check thickness of brake pads, front and rear		AP42.10-P-4253A
	0	Correct tire inflation pressure and enter in bar or psi.		AP40.15-P-4061A
		LF RF LR RR bar/psi:		
		Wheels, brakes - Recommended		
	0	Remove and install wheels		AP40.10-P-4050SX
	0	Inspect tires for damage and splits, measu-		AP40.10-P-4051Z
		re tread depth, enter in mm: LF RF LR RR		
		LF RF LR RR outside		
		center		
		inside		
		Underside of vehicle - Required		
† '	Ť ()	Leakage - Major components Check for chafe marks, line routing, damaged components i In the event of leakage, determine cause and perform repair via separate work order		AP00.20-P-0053SX
	0	Check front axle ball joints for play, check rubber boots		AP33.20-P-3353SX
	0			AP41.10-P-4152SX
	0	Inspect play of tie rod and drag link joints, inspect rubber boots		AP46.00-P-4653SX

	US Service		Not OK	
1 ↓	2 ↓		↓	
ide	Di	Vehicle front/rear - Recommended		
	0	Check and correct headlamp setting		AP82.10-P-8260SX
	0	Check wiper blade condition		AP82.30-P-8253G
		Trunk - Required		
	0	Correct inflation pressure in spare tire and enter in bar or psi. bar/psi:		AP40.15-P-4061A
		Trunk - Recommended		
	0	Check auxiliary battery condition using Midtronics battery tester. Attach Midtro- nics test report print out here		AP54.10-U-5453A
	0	Check trunk lighting		
		Engine compartment - Required		
	0	Leakage - Major components Check for chafe marks, line routing, damaged components in the event of leakage, determine cause and perform repair via separate work order		AP00.20-P-00535X
	0	Check catch, safety catch and hinges on engine hood for proper operation.		AP88.40-P-8851SX
	0	Clean water drain in air/water duct		AP83.10-P-8339M
	0	Check condition of poly-V-belt		AP13.22-P-1352SZ
		Check fluid level, correct as required i If there is a loss of fluid, determine cause and perform repair via separate work order		
	0	Engine cooling system, antifreeze and corrosion protection (engine 275 main circuit)		AH20.00-P-1142-01V
	0	Brake system		AP42.10-P-4210SX
	0	Power steering		AP46.00-P-4611SX
	0	Active Body Control CODE 487 (Active Body Control (ABC))		AP32.50-P-3213SX
	0	Windshield washer system (incl. summer/winter cleanser)		AP82.35-P-8210SX
		Engine compartment - Recommended		
	0	Starter battery, check and correct fluid level		AP54.10-P-5410SX
	0	Check starter battery condition using Mid- tronics battery tester. Attach Midtronics test report print out here		AP54.10-U-5453A

	Additional Work		
Completed ⊠	I	No	ot OK
↓			<u> </u>
US Service 3 Required	every 10,000 mi or 1 year: Engine compartment		
	Engine - oil and filter change		
		Engine 275.953	AP18.00-P-0101SZA
		Engine 275.982	AP18.00-P-0101SZB
US Service 4 Required	every 2 years: Engine compartment		
	Replace brake fluid		AP42.00-P-4280SX
US Service 4 Recommended	every 2 years:		
	Check bodywork for paint work damage by service advisor		☐ AP98.00-P-9850SX
	Underside of vehicle		
	Chassis and load-bearing body components: Check for damage and corrosion by service advisor		☐ AP00.20-P-0090SX
US Service 5 Required	every 30,000 mi or 2 years: Passenger compartment		
	Replace combination filter		AP83.00-P-8384SX
US Service 6 & 7	not applicable		
US Service 8 Required	every 40,000 mi or 4 years: Engine compartment		
	Replace engine air-cleaner insert		AP09.10-P-0980SZ
US Service 9 Recommended	every 5 years: Passenger compartment		
	Tilting/sliding roof: Clean slide rail and sli- de block except CODE 413 (Panoramic glass roof with top sliding roof)		AP77.20-P-7731SX
US Service 10 Recommended	every 3 years: Passenger compartment		
	Panoramic sliding roof - clean and lubricate quide mechanism CODE 413 (Panoramic glass roof with top sliding roof)		AP77.20-P-7732SX
US Service 11 Required	every 150,000 mi or 15 years: Passenger compartment		
	Replace fuel filter		AP47.20-P-0780SX
US Service 12 Required	every 60,000 mi or 5 years: Engine compartment		
	Replace spark plugs		AP15.10-P-1580SZ
US Service 13 Required	every 150,000 mi or 15 years: Engine compartment		
	Replace coolant (engine 275 low temperature circuit)		AP20.00-P-2080SZ

Completed ⊠		Not OK
↓		↓
US Service 14	every 3 years:	
Required	Engine compartment	
	Replace coolant	AP20.00-P-2080SZ
	(engine 275 main circuit)	
US Service 15 - 19	not applicable	
US Service 20	once at 40,000 mi:	
Required	Underside of vehicle	
	Automatic transmission - oil and filter	AP27.00-P-2702SX
	change	