

Mercedes-Benz

AP00.20-U-1208IM SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

Model	Year	201	7
USA			

Model 222



Customer:			Repair order num	nber:	
Tire Rotation (non-staggered width wheel setup only)	A 5,000-mile recommended likely necessitate tire rotation each 10,000-mile maintenance substitution of the state of the st	on at least once in between ince service and at every	Tires rotated	YES	NO
Note: For any cc	ondition found while performing the repair using a separate	ng the checks or inspections e repair order.	s included in this m	aintenance shee	t, determine
Current mileage read	ing:	O	il grade/viscosity:		
Additional notes:					
Service work to be pe service advisor:	erformed as advised by	Completion date:	Confirm work has below:	been performed	by signing

Required Service Work miles (thousands) Performed years (check if performed)	2	10 1	20 2	30	40 4	50 5	60 6	70 7	80 8	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
Reset maintenance service indicator in instrument cluster		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0043HA
Replace combination filter			•		•		•		•		•		•		•			AP83.00-P-8384HA
☐ Perform brake test		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.00-P-4290BA
☐ Engine – oil and filter change engine 157		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101EWG
engine 276		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101CWZ
engine 277		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101HC
engine 278		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101EW
engine 279		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•]	AP18.00-P-0101HA
Check condition of poly-V-belt Except model 222.163 (Hybrid)			•		•		•		•		•		•		•			AP13.22-P-1352EW
☐ Inspect trailer hitch condition and function with CODE 550 (Trailer hitch)			•		•		•		•		•		•		•			AP31.11-P-3152HA
☐ Check thickness of brake pads front and rear			•		•		•		•		•		•		•			AP42.10-P-4252HA
☐ Check and correct all tire air pressures, including spare where applicable		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.15-P-4061A
☐ Check vehicle underside for leaks and damage			•		•		•		•		•		•		•			AP00.20-P-0054J
Check all visible engine components for leaks and damage			•		•		•		•		•		•		•			AP00.20-P-0055A
☐ Inspect front axle and front axle ball joints, check rubber boots			•		•		•		•		•		•		•			AP33.10-P-3358C
☐ Inspect rear axle and rear axle ball joints, check rubber boots			•		•		•		•		•		•		•			AP35.20-P-3552C
☐ Inspect steering and tie rods, inspect rubber boots			•		•		•		•		•		•		•			AP46.00-P-4651C
☐ Inspect suspension struts or shock absorbers and springs																		
Except CODE 487 (Active Body Control)			•		•		•		•		•		•		•			AP32.25-P-3255B
With CODE 487 (Active Body Control)			•		•		•		•		•		•		•			AP32.25-P-3255BS
☐ Inspect driveshaft flexible discs			•		•		•		•		•		•		•			AP41.10-P-4152HA
☐ Check catch, safety catch and hinges on engine hood for proper operation		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Clean visible area of water deflector		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Active Body Control - check fluid level and correct if necessary with CODE 487 (Active Body Control (ABC))		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP32.50-P-3213HA
Check coolant level in coolant expansion reservoir for high-voltage Model 222.163 (Hybrid)			•		•		•		•		•		•		•			AP20.30-P-2053A
☐ Check coolant level and correct if necessary ☐ refer to AH20.00-P-1142-01LFB and AH20.00-P-1142-01MUB ☐ observe correct coolant composition			•		•		•		•		•		•		•			
☐ Check windshield washer system fluid, correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8210HA
Check brake fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4210HA
Replace brake fluid			•		•		•		•		•		•		•			AP42.00-P-4280HA
☐ Check charging cable and vehicle socket for mechanical damage Model 222.163 (Hybrid)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.10-P-5458B
☐ Check first aid kit		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP68.00-P-6850EW
☐ Check starter. Use MB diagnosis tool. Model 222.163 (Hybrid)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP15.30-P-1550AA

Required Service Work miles (thousands) Performed years (check if performed)	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK	
Reset Maintenance service indicator in instrument cluster I reminder - if not yet performed		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0043HA
Required Additional Work miles (thousands) Performed years (check if performed)	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
Replace main circuit coolant engine 277, 279				•			•			•			•			•		AP20.00-P-2082J
Replace air filter engine 157, 279 engine 157				•			•			•			•			•		AP09.10-P-0980AB
engine 279 □ Replace air filter				•			•			•			•			•		AP09.10-P-0980SZ
engine 276, 277, 278 engine 276 engine 277 engine 278 Automatic transmission - oil and filter change engine 157 with NAG2-V Sport and wet start-up clutch and engine 279 NAG2-VFE+				•		•	•			•	•		•			• • •		AP09.10-P-0980E AP09.10-P-0980SZ AP09.10-P-0980AB AP27.00-P-2702W
(transmission 722.9) Automatic transmission - oil and filter change engine 276, 277, 278 engine 276 with transmission 724.2 engine 278 with NAG2-FE+ and engine 277 with NAG2-VFE+ (transmission 722.9)							•						•					AP27.00-P-2702A AP27.00-P-2702W
Replace spark plugs engine 157, 276, 278 engine 277, 279						•					•					•		AP15.10-P-1580HA AP15.10-P-1580AAA
□ Replace fuel filter													•					AP47.20-P-0780HC
Replace main circuit coolant engine 157, 276, 278													•					AP20.00-P-2082J
Replace low-temperature circuit coolant i observe correct coolant compositio engine 157, 278 engine 276 engine 277, 279													• • •					AP20.00-P-2083H AP20.00-P-2083I AP20.00-P-2083A
Recommended Service miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
Work ☑ Performed years (check if performed)		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK ↓	
☐ Check horn		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check warning/indicator lamps		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5451HA
☐ Check illumination and interior lighting		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5453HA
☐ Check seatbelts and buckles for proper operation or damage			•		•		•		•		•		•		•			
☐ Check windshield wiper, washer and headlamp washer system operation		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8252HA
Replace wiper blades		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof)			•		•		•		•		•		•		•			AP77.20-P-7732HA

Recommended Service miles (thousands) Work	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
Performed years		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK	
(check if performed)																	Ψ	
☐ Activate Tire Pressure Monitoring System ☐ refer to vehicle Operator's Manual		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check all exterior lights		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.10-P-8252EW
☐ Check for body paint damage			•		•		•		•		•		•		•			AP60.00-P-0050LF
☐ Check TIREFIT tire sealant expiration date (where applicable)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4054R
☐ Check trunk / cargo area light		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check operation of headlamp range adjustment			•		•		•		•		•		•		•			AP82.10-P-8250EW
☐ Check headlamp setting, correct if necessary			•		•		•		•		•		•		•			AP82.10-P-8260HA
☐ Check battery condition. Attach printout to sheet models 222.163/182/185/976		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.10-U-5453A
☐ Tire rotation (where applicable)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check thickness of brake pads and discs, front and rear wheels removed																		
Pads		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4252HA
Discs (except CODE B07)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4258HA
Discs (CODE B07)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4258HC
☐ Visually inspect brake system components, hoses, lines and calipers		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Inspect tires for damage and measure remaining tread life		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4051EW
☐ Check chassis and load bearing body components for damage and corrosion			•		•		•		•		•		•		•			
☐ Check ex-factory driving aids (where applicable)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP86.20-P-8649U
☐ Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
After consultation with customer				_		4.0												
High Mileage Required Service Work at 1											_	20,0	000	mile	s or	2 ye	ars	
I Plus any applicable additional work list☑ Performed	ste	d a	th	e er	nd c	of th	ne s	erv	rice	sh	eet						Not OK	
(check if performed)																	Ψ	
Reset maintenance service indicator in in	stri	ume	ent o	clus	ter													AP00.20-P-0043HA
Replace combination filter																		AP83.00-P-8384HA
☐ Perform brake test																		AP42.00-P-4290BA
□ Engine – oil and filter change engine 157																		AP18.00-P-0101EWG
engine 276																		AP18.00-P-0101CWZ
engine 277																		AP18.00-P-0101HC
engine 278																		AP18.00-P-0101EW
engine 279																		AP18.00-P-0101HA
☐ Check condition of poly-V-belt Except model 222.163 (Hybrid)																		AP13.22-P-1352EW
☐ Inspect trailer hitch condition and function with CODE 550 (Trailer hitch)	1																	AP31.11-P-3152HA
Check thickness of brake pads front and	rea	ır																AP42.10-P-4252HA
☐ Check and correct all tire air pressures, in			q sı	oare	e wł	nere	e an	plic	abl	—— е								AP40.15-P-4061A
☐ Check vehicle underside for leaks and da			J - 1															AP00.20-P-0054J

\square Check all visible engine components for leaks and damage		AP00.20-P-0055A
☐ Inspect front axle and front axle ball joints, check rubber boots		AP33.10-P-3358C
☐ Inspect rear axle and rear axle ball joints, check rubber boots		AP35.20-P-3552C
☐ Inspect steering and tie rods, inspect rubber boots		AP46.00-P-4651C
☐ Inspect suspension struts or shock absorbers and springs		
Except CODE 487 (Active Body Control)		AP32.25-P-3255B
With CODE 487 (Active Body Control)		AP32.25-P-3255BS
☐ Inspect driveshaft flexible discs		AP41.10-P-4152HA
☐ Check catch, safety catch and hinges on engine hood for proper operation		
Clean visible area of water deflector		
☐ Active Body Control - check fluid level and correct if necessary with CODE 487 (Active Body Control (ABC))		AP32.50-P-3213HA
☐ Check coolant level in coolant expansion reservoir for high-voltage Model 222.163 (Hybrid)		AP20.30-P-2053A
Check coolant level and correct if necessary		
i refer to AH20.00-P-1142-01LFB and AH20.00-P-1142-01MUB		
i observe correct coolant composition		*D00 05 D 0010UA
Check windshield washer system fluid, correct if necessary		AP82.35-P-8210HA
Check brake fluid level and correct if necessary		AP42.10-P-4210HA
Replace brake fluid		AP42.00-P-4280HA
☐ Check charging cable and vehicle socket for mechanical damage Model 222.163 (Hybrid)		AP54.10-P-5458B
☐ Check first aid kit		AP68.00-P-6850EW
☐ Check starter. Use MB diagnosis tool.		AP15.30-P-1550AA
Model 222.163 (Hybrid)		
Model 222.163 (Hybrid) Reset Maintenance service indicator in instrument cluster i reminder - if not yet performed		AP00.20-P-0043HA
Reset Maintenance service indicator in instrument cluster	les or 2 yea	
Reset Maintenance service indicator in instrument cluster i reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 mi i Plus any applicable additional work listed at the end of the service sheet	-	ırs
Reset Maintenance service indicator in instrument cluster i reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 mi Plus any applicable additional work listed at the end of the service sheet Performed	Not Ok	ırs
Reset Maintenance service indicator in instrument cluster il reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles and applicable additional work listed at the end of the service sheet Performed (check if performed)	Not Ok	ırs
□ Reset Maintenance service indicator in instrument cluster	Not Ok	irs (
□ Reset Maintenance service indicator in instrument cluster	Not Ok	AP54.30-P-5451HA
□ Reset Maintenance service indicator in instrument cluster i reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 mi i Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) □ Check horn □ Check warning/indicator lamps □ Check illumination and interior lighting	Not Ok	irs (
□ Reset Maintenance service indicator in instrument cluster	Not Ok	AP54.30-P-5451HA AP54.30-P-5453HA
□ Reset Maintenance service indicator in instrument cluster i reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 mi i Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) □ Check horn □ Check warning/indicator lamps □ Check illumination and interior lighting	Not Ok	AP54.30-P-5451HA
□ Reset Maintenance service indicator in instrument cluster	Not Ok	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA
□ Reset Maintenance service indicator in instrument cluster	Not Ok	AP54.30-P-5451HA AP54.30-P-5453HA
Reset Maintenance service indicator in instrument cluster il reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 16 year	Not Ok	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA
□ Reset Maintenance service indicator in instrument cluster	Not Ok	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA
Reset Maintenance service indicator in instrument cluster i reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 mi Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check hom Check warning/indicator lamps Check illumination and interior lighting Check seatbelts and buckles for proper operation or damage Check windshield wiper, washer and headlamp washer system operation Replace wiper blades Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof) Activate Tire Pressure Monitoring System i refer to vehicle Operator's Manual	Not Ok	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA AP77.20-P-7732HA
Reset Maintenance service indicator in instrument cluster i reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 mi Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check seatbelts and buckles for proper operation or damage Check windshield wiper, washer and headlamp washer system operation Replace wiper blades Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof) Activate Tire Pressure Monitoring System i refer to vehicle Operator's Manual Check all exterior lights	Not Ok	AP54.30-P-5451HA AP54.30-P-5453HA AP54.30-P-5453HA AP82.35-P-8252HA AP77.20-P-7732HA
Reset Maintenance service indicator in instrument cluster i reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 mi Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check seatbelts and buckles for proper operation or damage Check windshield wiper, washer and headlamp washer system operation Replace wiper blades Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof) Activate Tire Pressure Monitoring System i refer to vehicle Operator's Manual Check all exterior lights Check for body paint damage	Not Ok	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA AP77.20-P-7732HA AP82.10-P-8252EW AP60.00-P-0050LF
Reset Maintenance service indicator in instrument cluster i reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 mi Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check seatbelts and buckles for proper operation or damage Check windshield wiper, washer and headlamp washer system operation Replace wiper blades Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof) Activate Tire Pressure Monitoring System i refer to vehicle Operator's Manual Check all exterior lights Check for body paint damage Check TIREFIT tire sealant expiration date (where applicable)	Not Ok □ □ □ □ □ □ □ □ □ □ □ □	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA AP77.20-P-7732HA AP82.10-P-8252EW AP60.00-P-0050LF
Reset Maintenance service indicator in instrument cluster i reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 mi Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check seatbelts and buckles for proper operation or damage Check windshield wiper, washer and headlamp washer system operation Replace wiper blades Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof) Activate Tire Pressure Monitoring System i refer to vehicle Operator's Manual Check all exterior lights Check for body paint damage Check TIREFIT tire sealant expiration date (where applicable) Check trunk / cargo area light	Not Ok	AP54.30-P-5451HA AP54.30-P-5453HA AP54.30-P-5453HA AP82.35-P-8252HA AP77.20-P-7732HA AP82.10-P-8252EW AP60.00-P-0050LF AP40.10-P-4054R

☐ Tire rotation (where applicable)		
☐ Check thickness of brake pads and discs, front and rear wheels removed		
Pads		AP42.10-P-4252HA
Discs (except CODE B07)		AP42.10-P-4258HA
Discs (CODE B07)		AP42.10-P-4258HC
☐ Visually inspect brake system components, hoses, lines and calipers		
☐ Inspect tires for damage and measure remaining tread life		AP40.10-P-4051EW
☐ Check chassis and load bearing body components for damage and corrosion		
☐ Check ex-factory driving aids (where applicable)		AP86.20-P-8649U
Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO)		
After consultation with customer		
$High\ Mileage\ Required\ Service\ Work\ at\ 170,000\ miles\ or\ 17\ years;\ then\ every\ 20,000\ miles\ or\ 2$	years	
I Plus any applicable additional work listed at the end of the service sheet		_
Performed	Not OK	(
(check if performed)	Ψ	
Reset maintenance service indicator in instrument cluster		AP00.20-P-0043HA
☐ Perform brake test		AP42.00-P-4290BA
☐ Engine – oil and filter change		
engine 157		AP18.00-P-0101EWG
engine 276		AP18.00-P-0101CWZ
engine 277		AP18.00-P-0101HC
engine 278		AP18.00-P-0101EW
engine 279		AP18.00-P-0101HA
☐ Check and correct all tire air pressures, including spare where applicable		AP40.15-P-4061A
☐ Check catch, safety catch and hinges on engine hood for proper operation		
☐ Clean visible area of water deflector		
☐ Active Body Control - check fluid level and correct if necessary with CODE 487 (Active Body Control (ABC))		AP32.50-P-3213HA
☐ Check windshield washer system fluid, correct if necessary		AP82.35-P-8210HA
☐ Check brake fluid level and correct if necessary		AP42.10-P-4210HA
☐ Check charging cable and vehicle socket for mechanical damage Model 222.163 (Hybrid)		AP54.10-P-5458B
☐ Check first aid kit		AP68.00-P-6850EW
☐ Check starter. Use MB diagnosis tool. Model 222.163 (Hybrid)		AP15.30-P-1550AA
Reset Maintenance service indicator in instrument cluster ireminder - if not yet performed		AP00.20-P-0043HA
High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles	s or 2 yea	ırs
i Plus any applicable additional work listed at the end of the service sheet		
☑ Performed	Not OK	(
(check if performed)	Ψ	
☐ Check horn		
☐ Check warning/indicator lamps		AP54.30-P-5451HA
☐ Check illumination and interior lighting		AP54.30-P-5453HA
☐ Check windshield wiper, washer and headlamp washer system operation		AP82.35-P-8252HA
Replace wiper blades		
□ Activate Tire Pressure Monitoring System		
I refer to vehicle Operator's Manual		

☐ Check all exterior lights		AP82.10-P-8252EW
	(where applicable)	AP40.10-P-4054R
☐ Check TIREFIT tire sealant expiration date ☐ Check trunk / cargo area light	(where applicable)	74 10.101 100111
Check battery condition. Attach printout to s	cheet	AP54.10-U-5453A
models 222.163/182/185/976	nieet	
☐ Tire rotation (where applicable)		
\square Check thickness of brake pads and discs, fr	ont and rear wheels removed	
Pads		AP42.10-P-4252HA
Discs (except CODE B07)		AP42.10-P-4258HA
Discs (CODE B07)		 AP42.10-P-4258HC
\square Visually inspect brake system components,	hoses, lines and calipers	
\square Inspect tires for damage and measure rema	aining tread life	AP40.10-P-4051EW
☐ Check ex-factory driving aids (where applications)	able)	AP86.20-P-8649U
Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO)		
After consultation with customer		
High Mileage Additional Work		
⊠ Performed		
(check if performed)		
Replace main circuit coolant engine 277, 279	If more than 30,000 miles or 3 years since last replacement	AP20.00-P-2082J
Replace air filter engine 157, 279		
engine 157	If more than 30,000 miles or 3 years since last replacement	AP09.10-P-0980AB
engine 279	If more than 30,000 miles or 3 years since last replacement	AP09.10-P-0980SZ
Replace air filter engine 276, 277, 278		
engine 276	If more than 50,000 miles or 5 years since last replacement	AP09.10-P-0980E
engine 277	If more than 50,000 miles or 5 years since last replacement	AP09.10-P-0980SZ
engine 278	If more than 50,000 miles or 5 years since last replacement	AP09.10-P-0980AB
Automatic transmission - oil and filter change engine 157 with NAG2-V Sport and wet start-up clutch and engine 279 NAG2-VFE+ (transmission 722.9)	If more than 30,000 miles or 3 years since last replacement	AP27.00-P-2702W
Automatic transmission - oil and filter change engine 276, 277, 278		
engine 276 with transmission 724.2	If more than 60,000 miles or 6 years since last replacement	AP27.00-P-2702A
engine 278 with NAG2-FE+ and engine 277 with NAG2-VFE+ (transmission 722.9)	If more than 60,000 miles or 6 years since last replacement	AP27.00-P-2702W
Replace spark plugs		
engine 157, 276, 278	If more than 50,000 miles or 5 years since last replacement	AP15.10-P-1580HA
engine 277, 279	If more than 50,000 miles or 5 years since last replacement	AP15.10-P-1580AAA
Replace fuel filter	If more than 120,000 miles or 12 years since last replacement	AP47.20-P-0780HC
Replace main circuit coolant engine 157, 276, 278	If more than 120,000 miles or 12 years since last replacement	AP20.00-P-2082J
i observe correct coolant composition		
Replace low-temperature circuit coolant		
i observe correct coolant compositio		
engine 157, 278	If more than 120,000 miles or 12 years since last replacement	AP20.00-P-2083H
engine 276	If more than 120,000 miles or 12 years since last replacement	AP20.00-P-2083I
engine 277, 279	If more than 120,000 miles or 12 years since last replacement	AP20.00-P-2083A

Tire infl	Tire inflation pressure (bar/psi)												
LF	RF	LR	RR	Spare									

Tire tread depth (mm)												
	LF	RF	LR	RR								
outside												
center												
inside												