

## Mercedes-Benz

AP00.20-U-1208IK SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

Model	Year	201	5
USA			

## Model 222



Customer:			Repair order nur	mber:	
Tire Rotation (non-staggered width wheel setup only)	A 5,000-mile recommender likely necessitate tire rotation each 10,000-mile maintenance successions.	on at least once in between ance service and at every	Tires rotated	YES	NO
Note: For any co	ondition found while performing the repair using a separate	ng the checks or inspections e repair order.	s included in this m	naintenance shee	t, determine
Current mileage read	ding:	_ Oi	I grade/viscosity:_		
Additional notes:					
_					
Service work to be poservice advisor:	erformed as advised by		Confirm work has below:	been performed	by signing

Required Service Work miles (thousands)  Performed years (check if performed)	2	10 1	20 2	30	40 4	50 5	60 6	70 7	80 8	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK <b>↓</b>	
Reset Maintenance service indicator in instrument cluster		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0043HA
☐ Replace combination filter			•		•		•		•		•		•		•			AP83.00-P-8384HA
☐ Check parking brake (function only)			•		•		•		•		•		•		•			AP42.00-P-4290BA
☐ Engine – oil and filter change																		
engine 157		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101EWG
engine 276		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101CWZ
engine 277		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101HC
engine 278		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101EW
engine 279		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101HA
Check condition of poly-V-belt Except model 222.163 (Hybrid)			•		•		•		•		•		•		•			AP13.22-P-1352EW
☐ Inspect trailer hitch condition and function with CODE 550 (Trailer hitch)			•		•		•		•		•		•		•			AP31.11-P-3152HA
☐ Check thickness of brake pads front and rear			•		•		•		•		•		•		•			AP42.10-P-4252HA
☐ Check and correct all tire air pressures, including spare where applicable		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.15-P-4061A
☐ Check vehicle underside for leaks and damage			•		•		•		•		•		•		•			AP00.20-P-0054J
☐ Check all visible engine components for leaks			•		•		•		•		•		•		•			AP00.20-P-0055A
☐ Inspect front axle and front axle ball joints, check rubber boots			•		•		•		•		•		•		•			AP33.10-P-3358C
☐ Inspect rear axle and rear axle ball joints, check rubber boots			•		•		•		•		•		•		•			AP35.20-P-3552C
☐ Inspect steering and tie rods, inspect rubber boots			•		•		•		•		•		•		•			AP46.00-P-4651C
☐ Inspect suspension struts or shock absorbers and springs																		
Except CODE 487 (Active Body Control)			•		•		•		•		•		•		•			AP32.25-P-3255B
With CODE 487 (Active Body Control)			•		•		•		•		•		•		•			AP32.25-P-3255BS
☐ Inspect driveshaft flexible discs			•		•		•		•		•		•		•			AP41.10-P-4152HA
Check catch, safety catch and hinges on engine hood for proper operation		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Clean visible area of water deflector		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Active Body Control-check fluid level and correct if necessary  CODE 487 (Active Body Control (ABC))		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP32.50-P-3213HA
☐ Check coolant level in coolant expansion reservoir for high-voltage battery cooling circuit and correct if necessary  Model 222.163 (Hybrid)			•		•		•		•		•		•		•			AP20.30-P-2053A
☐ Check coolant level and correct if necessary  ☐ refer to AH20.00-P-1142-01LFB and AH20.00-P-1142-01MUB ☐ observe correct coolant composition			•		•		•		•		•		•		•			
☐ Check brake fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4210HA
Replace brake fluid			•		•		•		•		•		•		•			AP42.00-P-4280HA
☐ Check windshield washer system fluid, correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8210HA
☐ Check charging cable and vehicle socket for mechanical damage  Model 222.163 (Hybrid)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.10-P-5458B
Check starter. Use MB diagnosis tool. Model 222.163 (Hybrid)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP15.30-P-1550AA

Required Service Work miles (thousands)  Performed years (check if performed)	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK	
Reset Maintenance service indicator in instrument cluster  I reminder - if not yet performed		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0043HA
Required Additional Work miles (thousands)  Performed years (check if performed)	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90 9	100 10	110 11	120 12	130 13	140 14	150 15	Not OK <b>↓</b>	
Replace main circuit coolant engine 277, 279				•			•			•			•			•		AP20.00-P-2082J
☐ Replace air filter engine 157, 279 engine 157 engine 279				•			•			•			•			•		AP09.10-P-0980AB AP09.10-P-0980SZ
□ Automatic transmission-oil and filter change engine 157 with NAG2-V Sport and wet start-up clutch and engine 279 NAG2-VFE+ (transmission 722.9)				•			•			•			•			•		AP27.00-P-2702W
Automatic transmission-oil and filter change engine 276, 277, 278 engine 276 with transmission 724.2							•						•					AP27.00-P-2702A
engine 278 with NAG2-FE+ and engine 277 with NAG2-VFE+ (transmission 722.9)							•						•					AP27.00-P-2702W
Replace air filter engine 276, 277, 278 engine 276 engine 277						•					•					•		AP09.10-P-0980E AP09.10-P-0980SZ
engine 278						•					•					•		AP09.10-P-0980AB
engine 157, 276, 278 engine 277, 279						•					•					•		AP15.10-P-1580HA AP15.10-P-1580AAA
Replace fuel filter						•					•		•			•		AP47.20-P-0780HC
Replace main circuit coolant engine 157, 276, 278  i observe correct coolant composition													•					AP20.00-P-2082J
Replace low-temperature circuit coolant  i observe correct coolant composition engine 157, 278 engine 276 engine 277, 279													• •					AP20.00-P-2083H AP20.00-P-2083I AP20.00-P-2083A
Recommended Service miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		7.11 20.00 7 20007
Work  ☑ Performed years (check if performed)		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK <b>↓</b>	
☐ Check horn		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check warning/indicator lamps		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5451HA
Check illumination and interior lighting		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5453HA
Check seatbelts and buckles for proper operation or damage			•		•		•		•		•		•		•			
Check windshield wiper, washer and headlamp washer system operation		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8252HA
Replace wiper blades		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof)			•		•		•		•		•		•		•			AP77.20-P-7732HA

Recommended Service miles (thousands) Work	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
Performed years (check if performed)		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK <b>↓</b>	
Activate Tire Pressure Monitoring System  Trefer to vehicle Operator's Manual		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check all exterior lights		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.10-P-8252EW
☐ Check for body paint damage			•		•		•		•		•		•		•			
☐ Check TIREFIT tire sealant expiration date (where applicable)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4054R
☐ Check trunk / cargo area light		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
$\square$ Check headlamp setting, correct if necessary			•		•		•		•		•		•		•			AP82.10-P-8260HA
☐ Check battery condition. Attach printout to sheet models 222.163/182/185		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.10-U-5453A
☐ Tire rotation (where applicable)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check thickness of brake pads and discs, front and rear wheels removed  Pads																_	П	AD42 40 D 4252HA
		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4252HA AP42.10-P-4258HA
Discs (except CODE B07)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Discs (CODE B07)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4258HC
☐ Visually inspect brake system components, hoses, lines and calipers		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AD40 40 D 4054514
☐ Inspect tires for damage and measure remaining tread life		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4051EW
☐ Check chassis and load bearing body components for damage and corrosion			•		•		•		•		•		•		•			
High Mileage Required Service Work at 1	60.0	000	mi	les	or '	16 v	/eai	rs: 1	the	n ev	/erv	20.0	000 i	mile	s or	2 ve	ars	
High Mileage Required Service Work at 10  Plus any applicable additional work list Performed (check if performed)						_					-	20,0	)00 i	mile	s or	2 ye	ears Not OK <b>↓</b>	
i Plus any applicable additional work lis  Performed	sted	d at	t the	e er	nd c	_					-	20,0	000 i	mile	s or	2 ye	Not OK	AP00.20-P-0043HA
■ Plus any applicable additional work lis ■ Performed (check if performed)	sted	d at	t the	e er	nd c	_					-	20,0	000 i	mile	s or	2 ye	Not OK	
■ Plus any applicable additional work lis ■ Performed (check if performed)  □ Reset Maintenance service indicator in in	sted	d at	t the	e er	nd c	_					-	20,0	000 1	mile	s or	2 ye	Not OK	AP00.20-P-0043HA
I Plus any applicable additional work lis	sted	d at	t the	e er	nd c	_					-	20,0	000 1	mile	s or	2 уе	Not OK ↓	AP00.20-P-0043HA AP83.00-P-8384HA AP42.00-P-4290BA  AP18.00-P-0101EWG AP18.00-P-0101CWZ AP18.00-P-0101HC AP18.00-P-0101EW AP18.00-P-0101HA
I Plus any applicable additional work lis	sted	d at	t the	e er	nd c	_					-	20,0	000 1	mile	s or	2 уе	Not OK	AP00.20-P-0043HA AP83.00-P-8384HA AP42.00-P-4290BA  AP18.00-P-0101EWG AP18.00-P-0101CWZ AP18.00-P-0101HC AP18.00-P-0101EW
I Plus any applicable additional work lis	stru	d at	t the	e er	nd c	_					-	20,0	000 1	mile	s or	2 уе	Not OK ↓	AP00.20-P-0043HA AP83.00-P-8384HA AP42.00-P-4290BA  AP18.00-P-0101EWG AP18.00-P-0101CWZ AP18.00-P-0101HC AP18.00-P-0101EW AP18.00-P-0101HA
I Plus any applicable additional work lis  Performed (check if performed)  Reset Maintenance service indicator in in  Replace combination filter  Check parking brake (function only)  Engine − oil and filter change engine 157 engine 276 engine 277 engine 278 engine 278 engine 279  Check condition of poly-V-belt Except model 222.163 (Hybrid)  Inspect trailer hitch condition and function	stru	ume	t the	e er	nd c	_					-	20,0		mile	s or	2 уе	Not OK	AP00.20-P-0043HA AP83.00-P-8384HA AP42.00-P-4290BA  AP18.00-P-0101EWG AP18.00-P-0101CWZ AP18.00-P-0101HC AP18.00-P-0101EW AP18.00-P-0101HA AP13.22-P-1352EW
I Plus any applicable additional work lis	stru	ume	t the	clus	ter	of th	ne s	serv	rice	she	-	20,0	0000 1	mile	s or	2 ye	Not OK	AP00.20-P-0043HA AP83.00-P-8384HA AP42.00-P-4290BA  AP18.00-P-0101EWG AP18.00-P-0101CWZ AP18.00-P-0101HC AP18.00-P-0101EW AP18.00-P-0101HA AP13.22-P-1352EW  AP31.11-P-3152HA
I Plus any applicable additional work lis  Performed (check if performed)  Reset Maintenance service indicator in in  Replace combination filter  Check parking brake (function only)  Engine − oil and filter change engine 157 engine 276 engine 277 engine 278 engine 279  Check condition of poly-V-belt Except model 222.163 (Hybrid)  Inspect trailer hitch condition and function with CODE 550 (Trailer hitch)  Check thickness of brake pads front and in	stru	ume	t the	clus	ter	of th	ne s	serv	rice	she	-	20,0	0000 1	mile	s or	2 ye	Not OK	AP00.20-P-0043HA AP83.00-P-8384HA AP42.00-P-4290BA  AP18.00-P-0101EWG AP18.00-P-0101CWZ AP18.00-P-0101HC AP18.00-P-0101HA AP13.22-P-1352EW  AP31.11-P-3152HA AP42.10-P-4252HA
I Plus any applicable additional work lis	stru	r ge	t the	clus	ter	of th	ne s	serv	rice	she	-	20,0	0000 1	mile	s or	2 ye	Not OK	AP00.20-P-0043HA AP83.00-P-8384HA AP42.00-P-4290BA  AP18.00-P-0101EWG AP18.00-P-0101CWZ AP18.00-P-0101HC AP18.00-P-0101EW AP18.00-P-0101HA AP13.22-P-1352EW  AP31.11-P-3152HA AP42.10-P-4252HA AP40.15-P-4061A
I Plus any applicable additional work lis  Performed (check if performed)  Reset Maintenance service indicator in in  Replace combination filter  Check parking brake (function only)  Engine − oil and filter change engine 157 engine 276 engine 277 engine 278 engine 279  Check condition of poly-V-belt Except model 222.163 (Hybrid)  Inspect trailer hitch condition and function with CODE 550 (Trailer hitch)  Check thickness of brake pads front and in  Check vehicle underside for leaks and da	stru stru real	r iding	g s	clus	ter	of th	e ap	serv	rice	she	-	20,0	0000 1	mile	s or	2 ye	Not OK	AP00.20-P-0043HA AP83.00-P-8384HA AP42.00-P-4290BA  AP18.00-P-0101EWG AP18.00-P-0101CWZ AP18.00-P-0101HC AP18.00-P-0101HA AP13.22-P-1352EW  AP31.11-P-3152HA AP42.10-P-4252HA AP40.15-P-4061A AP00.20-P-0054J
I Plus any applicable additional work lise  Performed (check if performed)  □ Reset Maintenance service indicator in in □ Replace combination filter  □ Check parking brake (function only)  □ Engine – oil and filter change engine 157 engine 276 engine 277 engine 278 engine 279  □ Check condition of poly-V-belt Except model 222.163 (Hybrid)  □ Inspect trailer hitch condition and function with CODE 550 (Trailer hitch)  □ Check thickness of brake pads front and □ Check and correct all tire air pressures, in □ Check vehicle underside for leaks and dat □ Check all visible engine components for leaks and data.	stru stru real mclu uma eak	r idinge	g s	clus	ter	of th	e ap	serv	rice	she	-	20,0	0000 1	mile	s or	2 ye	Not OK	AP00.20-P-0043HA AP83.00-P-8384HA AP42.00-P-4290BA  AP18.00-P-0101EWG AP18.00-P-0101CWZ AP18.00-P-0101HC AP18.00-P-0101HA AP13.22-P-1352EW  AP31.11-P-3152HA AP42.10-P-4252HA AP40.15-P-4061A AP00.20-P-0055A
I Plus any applicable additional work lis  Performed (check if performed)  Reset Maintenance service indicator in in  Replace combination filter  Check parking brake (function only)  Engine − oil and filter change engine 157 engine 276 engine 277 engine 278 engine 279  Check condition of poly-V-belt Except model 222.163 (Hybrid)  Inspect trailer hitch condition and function with CODE 550 (Trailer hitch)  Check thickness of brake pads front and in  Check and correct all tire air pressures, in  Check all visible engine components for le  Inspect front axle and front axle ball joints	stru stru real nclu ima eak s, ch	r reddingers sheeck	g s	clus	ter	of th	e ap	serv	rice	she	-	20,0		mile	s or	2 ye	Not OK	AP00.20-P-0043HA AP83.00-P-8384HA AP42.00-P-4290BA  AP18.00-P-0101EWG AP18.00-P-0101CWZ AP18.00-P-0101HC AP18.00-P-0101HA AP13.22-P-1352EW  AP31.11-P-3152HA AP42.10-P-4252HA AP40.15-P-4061A AP00.20-P-0055A AP33.10-P-3358C

With CODE 487 (Active Body Control)		AP32.25-P-3255BS
☐ Inspect driveshaft flexible discs		AP41.10-P-4152HA
☐ Check catch, safety catch and hinges on engine hood for proper operation		
☐ Clean visible area of water deflector		
Active Body Control-check fluid level and correct if necessary CODE 487 (Active Body Control (ABC))		AP32.50-P-3213HA
Check coolant level in coolant expansion reservoir for high-voltage battery cooling circuit and correct if necessary  Model 222.163 (Hybrid)		AP20.30-P-2053A
☐ Check coolant level and correct if necessary  i refer to AH20.00-P-1142-01LFB and AH20.00-P-1142-01MUB i observe correct coolant composition		
☐ Check brake fluid level and correct if necessary		AP42.10-P-4210HA
Replace brake fluid		AP42.00-P-4280HA
☐ Check windshield washer system fluid, correct if necessary		AP82.35-P-8210HA
☐ Check charging cable and vehicle socket for mechanical damage Model 222.163 (Hybrid)		AP54.10-P-5458B
☐ Check starter. Use MB diagnosis tool.  Model 222.163 (Hybrid)		AP15.30-P-1550AA
Reset Maintenance service indicator in instrument cluster  irreminder - if not yet performed		AP00.20-P-0043HA
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles	or 2 yea	rs
i Plus any applicable additional work listed at the end of the service sheet		
Performed	Not OK	
(check if performed)		
Check horn		AD54.00 D 545411A
Check warning/indicator lamps		AP54.30-P-5451HA
☐ Check illumination and interior lighting		AP54.30-P-5453HA
Check seatbelts and buckles for proper operation or damage		
Check windshield wiper, washer and headlamp washer system operation		AP82.35-P-8252HA
Replace wiper blades		
☐ Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof)		AP77.20-P-7732HA
☐ Activate Tire Pressure Monitoring System  ☐ refer to vehicle Operator's Manual		
☐ Check all exterior lights		AP82.10-P-8252EW
☐ Check for body paint damage		
☐ Check TIREFIT tire sealant expiration date (where applicable)		AP40.10-P-4054R
☐ Check trunk / cargo area light		
☐ Check headlamp setting, correct if necessary		AP82.10-P-8260HA
☐ Check battery condition. Attach printout to sheet		
models 222.163/182/185		AP54.10-U-5453A
models 222.163/182/185  Tire rotation (where applicable)		AP54.10-U-5453A
		AP54.10-U-5453A
☐ Tire rotation (where applicable)		AP54.10-U-5453A  AP42.10-P-4252HA
☐ Tire rotation (where applicable) ☐ Check thickness of brake pads and discs, front and rear wheels removed Pads Discs (except CODE B07)		AP42.10-P-4252HA AP42.10-P-4258HA
☐ Tire rotation (where applicable)  ☐ Check thickness of brake pads and discs, front and rear wheels removed Pads Discs (except CODE B07) Discs (CODE B07)		AP42.10-P-4252HA
☐ Tire rotation (where applicable) ☐ Check thickness of brake pads and discs, front and rear wheels removed Pads Discs (except CODE B07)		AP42.10-P-4252HA AP42.10-P-4258HA

$\square$ Check chassis and load bearing body components for damage and corrosion		
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or 2	years	
i Plus any applicable additional work listed at the end of the service sheet		
☑ Performed	Not OK	
(check if performed)	•	
Reset Maintenance service indicator in instrument cluster		AP00.20-P-0043HA
☐ Engine – oil and filter change		
engine 157		AP18.00-P-0101EWG
engine 276		AP18.00-P-0101CWZ
engine 277		AP18.00-P-0101HC
engine 278		AP18.00-P-0101EW
engine 279		AP18.00-P-0101HA
Check and correct all tire air pressures, including spare where applicable		AP40.15-P-4061A
Check catch, safety catch and hinges on engine hood for proper operation		
Clean visible area of water deflector		
☐ Active Body Control-check fluid level and correct if necessary CODE 487 (Active Body Control (ABC))		AP32.50-P-3213HA
☐ Check brake fluid level and correct if necessary		AP42.10-P-4210HA
☐ Check windshield washer system fluid, correct if necessary		AP82.35-P-8210HA
☐ Check charging cable and vehicle socket for mechanical damage  Model 222.163 (Hybrid)		AP54.10-P-5458B
☐ Check starter. Use MB diagnosis tool.  Model 222.163 (Hybrid)		AP15.30-P-1550AA
Reset Maintenance service indicator in instrument cluster		AP00.20-P-0043HA
l <u>—</u>		, co. <u>-</u> c . co .c
i reminder - if not yet performed	es or 2 vea	
i reminder - if not yet performed  High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles	es or 2 yea	
i reminder - if not yet performed  High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 mile  Plus any applicable additional work listed at the end of the service sheet	es or 2 yea	ırs
i reminder - if not yet performed  High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles		ırs
i reminder - if not yet performed  High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 mile  Plus any applicable additional work listed at the end of the service sheet  Performed	Not OK	ırs
i reminder - if not yet performed  High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles  Plus any applicable additional work listed at the end of the service sheet  Performed (check if performed)	Not OK	ırs
i reminder - if not yet performed  High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles  Plus any applicable additional work listed at the end of the service sheet  Performed (check if performed)  □ Check horn	Not OK	irs
i reminder - if not yet performed  High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles  Plus any applicable additional work listed at the end of the service sheet  Performed (check if performed)  □ Check horn  □ Check warning/indicator lamps	Not OK	AP54.30-P-5451HA
i reminder - if not yet performed  High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles  Plus any applicable additional work listed at the end of the service sheet  Performed (check if performed)  □ Check horn  □ Check warning/indicator lamps  □ Check illumination and interior lighting	Not Ok	AP54.30-P-5451HA AP54.30-P-5453HA
i reminder - if not yet performed  High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles  Plus any applicable additional work listed at the end of the service sheet  Performed (check if performed)  Check horn  Check warning/indicator lamps  Check illumination and interior lighting  Check windshield wiper, washer and headlamp washer system operation  Replace wiper blades  Activate Tire Pressure Monitoring System	Not Ok	AP54.30-P-5451HA AP54.30-P-5453HA
I reminder - if not yet performed   High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles   I Plus any applicable additional work listed at the end of the service sheet   ☑ Performed (check if performed)   ☐ Check horn   ☐ Check warning/indicator lamps   ☐ Check illumination and interior lighting   ☐ Check windshield wiper, washer and headlamp washer system operation   ☐ Replace wiper blades   ☐ Activate Tire Pressure Monitoring System   I refer to vehicle Operator's Manual	Not Ok	AP54.30-P-5451HA AP54.30-P-5453HA
I reminder - if not yet performed         High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles         I Plus any applicable additional work listed at the end of the service sheet         ⊠ Performed (check if performed)         □ Check horn         □ Check warning/indicator lamps         □ Check illumination and interior lighting         □ Check windshield wiper, washer and headlamp washer system operation         □ Replace wiper blades         □ Activate Tire Pressure Monitoring System         I refer to vehicle Operator's Manual         □ Check all exterior lights	Not OK	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA
I reminder - if not yet performed   High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles   I Plus any applicable additional work listed at the end of the service sheet   ☑ Performed (check if performed)   ☐ Check horn   ☐ Check warning/indicator lamps   ☐ Check illumination and interior lighting   ☐ Check windshield wiper, washer and headlamp washer system operation   ☐ Replace wiper blades   ☐ Activate Tire Pressure Monitoring System   I refer to vehicle Operator's Manual   ☐ Check all exterior lights   ☐ Check TIREFIT tire sealant expiration date (where applicable)	Not OK	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA
I reminder - if not yet performed         High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles         I Plus any applicable additional work listed at the end of the service sheet         ⊠ Performed (check if performed)         □ Check horn         □ Check warning/indicator lamps         □ Check illumination and interior lighting         □ Check windshield wiper, washer and headlamp washer system operation         □ Replace wiper blades         □ Activate Tire Pressure Monitoring System         I refer to vehicle Operator's Manual         □ Check all exterior lights	Not OK	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA
Ill reminder - if not yet performed         High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles         Ill Plus any applicable additional work listed at the end of the service sheet         Image: Performed (check if performed)         Image: Check hore         Image: Check warning/indicator lamps         Image: Check illumination and interior lighting         Image: Check windshield wiper, washer and headlamp washer system operation         Image: Replace wiper blades         Image: Activate Tire Pressure Monitoring System         Image: Replace wiper blades         Image: Activate Tire Pressure Monitoring System         Image: Replace wiper blades         Image: Activate Tire Pressure Monitoring System         Image: Replace wiper blades         Image: Replace wipe	Not OK	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA AP82.10-P-8252EW AP40.10-P-4054R
ii reminder - if not yet performed  High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles ii Plus any applicable additional work listed at the end of the service sheet  Performed (check if performed)  Check horn  Check warning/indicator lamps  Check illumination and interior lighting  Check windshield wiper, washer and headlamp washer system operation  Replace wiper blades  Activate Tire Pressure Monitoring System ii refer to vehicle Operator's Manual  Check all exterior lights  Check TIREFIT tire sealant expiration date (where applicable)  Check battery condition. Attach printout to sheet models 222.163/182/185	Not OK	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA AP82.10-P-8252EW AP40.10-P-4054R
ii reminder - if not yet performed  High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles  ii Plus any applicable additional work listed at the end of the service sheet  iii Performed (check if performed)  Check horn  Check warning/indicator lamps  Check illumination and interior lighting  Check windshield wiper, washer and headlamp washer system operation  Replace wiper blades  Activate Tire Pressure Monitoring System ii refer to vehicle Operator's Manual  Check all exterior lights  Check TIREFIT tire sealant expiration date (where applicable)  Check battery condition. Attach printout to sheet models 222.163/182/185  □ Tire rotation (where applicable)	Not OK	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA AP82.10-P-8252EW AP40.10-P-4054R
### Ireminder - if not yet performed  ### High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles    Plus any applicable additional work listed at the end of the service sheet   Performed (check if performed)    Check horn   Check warning/indicator lamps   Check illumination and interior lighting   Check windshield wiper, washer and headlamp washer system operation   Replace wiper blades   Activate Tire Pressure Monitoring System   Performed in the pressure Monitoring System in the pressure Monitoring Monitoring Monitoring Monitoring Monitor	Not OK	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA  AP82.10-P-8252EW AP40.10-P-4054R  AP54.10-U-5453A
High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 miles  Plus any applicable additional work listed at the end of the service sheet  Performed (check if performed)  Check horn  Check warning/indicator lamps  Check illumination and interior lighting  Check windshield wiper, washer and headlamp washer system operation  Replace wiper blades  Activate Tire Pressure Monitoring System  refer to vehicle Operator's Manual  Check all exterior lights  Check TIREFIT tire sealant expiration date (where applicable)  Check battery condition. Attach printout to sheet models 222.163/182/185  Tire rotation (where applicable)  Check thickness of brake pads and discs, front and rear wheels removed Pads	Not OK	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA  AP82.10-P-8252EW AP40.10-P-4054R  AP54.10-U-5453A

☐ Inspect tires for damage and measure rema	aining tread life	AP40.10-P-4051EW
High Mileage Additional Work  Performed (check if performed)		
Replace main circuit coolant engine 277, 279	If more than 30,000 miles or 3 years since last replacement	AP20.00-P-2082J
Replace air filter engine 157, 279		
engine 157	If more than 30,000 miles or 3 years since last replacement	AP09.10-P-0980AB
engine 279	If more than 30,000 miles or 3 years since last replacement	AP09.10-P-0980SZ
Automatic transmission-oil and filter change engine 157 with NAG2-V Sport and wet start-up clutch and engine 279 NAG2-VFE+ (transmission 722.9)	If more than 30,000 miles or 3 years since last replacement	AP27.00-P-2702W
Automatic transmission-oil and filter change engine 276, 277, 278		
engine 276 with transmission 724.2	If more than 60,000 miles or 6 years since last replacement	AP27.00-P-2702A
engine 278 with NAG2-FE+ and engine 277 with NAG2-VFE+ (transmission 722.9)	If more than 60,000 miles or 6 years since last replacement	AP27.00-P-2702W
Replace air filter engine 276, 277, 278		
engine 276	If more than 50,000 miles or 5 years since last replacement	AP09.10-P-0980E
engine 277	If more than 50,000 miles or 5 years since last replacement	AP09.10-P-0980SZ
engine 278	If more than 50,000 miles or 5 years since last replacement	AP09.10-P-0980AB
Replace spark plugs		
engine 157, 276, 278	If more than 50,000 miles or 5 years since last replacement	AP15.10-P-1580HA
engine 277, 279	If more than 50,000 miles or 5 years since last replacement	AP15.10-P-1580AAA
Replace fuel filter	If more than 120,000 miles or 12 years since last replacement	AP47.20-P-0780HC
Replace main circuit coolant engine 157, 276, 278	If more than 120,000 miles or 12 years since last replacement	AP20.00-P-2082J
i observe correct coolant composition		
Replace low-temperature circuit coolant		
i observe correct coolant composition		
engine 157, 278	If more than 120,000 miles or 12 years since last replacement	AP20.00-P-2083H
engine 276	If more than 120,000 miles or 12 years since last replacement	AP20.00-P-2083I
engine 277, 279	If more than 120,000 miles or 12 years since last replacement	AP20.00-P-2083A

Tire inflation pressure (bar/psi)									
LF	RF	LR	RR	Spare					

Tire trea	Tire tread depth (mm)										
	LF	RF	LR	RR							
outside											
center											
inside											