

Mercedes-Benz

AP00.20-U-1208IN SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

Model	Year	2018
USA		

Model 222



Customer:			Repair order num	nber:	
Tire Rotation (non-staggered width wheel setup only)	A 5,000-mile recommended likely necessitate tire rotation each 10,000-mile maintenance substitution of the state of the st	on at least once in between ince service and at every	Tires rotated	YES	NO
Note: For any co	ondition found while performin m the repair using a separate	ng the checks or inspections e repair order.	s included in this m	aintenance shee	t, determine
Current mileage read	ling:	_ _	I grade/viscosity:		
Additional notes:					
Service work to be poservice advisor:	erformed as advised by	Completion date:	Confirm work has below:	been performed	by signing

Required Service Work miles (thousands) Performed years (check if performed)	2	10 1	20 2	30	40 4	50 5	60 6	70 7	80 8	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ↓	
Reset maintenance service indicator in instrument cluster		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0043J
☐ Replace combination filter			•		•		•		•		•		•		•			AP83.00-P-8384HA
☐ Perform brake test		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.00-P-4290BA
☐ Engine – oil and filter change																		
engine 176		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101MNL
engine 177		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101DD
engine 276		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101CWZ
engine 279		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101HA
Check condition of poly-V-belt																		AD42 00 D 40505W
engine 276, 279			•		•		•		•		•		•		•			AP13.22-P-1352EW
engine 176, 177			•		•		•		•		•		•		•			AP13.22-P-1352D
☐ Inspect trailer hitch condition and function with CODE 550 (Trailer hitch)			•		•		•		•		•		•		•			AP31.11-P-3152HA
☐ Check thickness of brake pads front and rear			•		•		•		•		•		•		•			AP42.10-P-4252HA
☐ Check and correct all tire air pressures, including spare where applicable		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.15-P-4061A
☐ Check vehicle underside for leaks and damage			•		•		•		•		•		•		•			AP00.20-P-0054J
☐ Check all visible engine components for leaks and damage			•		•		•		•		•		•		•			AP00.20-P-0055A
☐ Inspect front axle and front axle ball joints, check rubber boots			•		•		•		•		•		•		•			AP33.10-P-3358C
☐ Inspect rear axle and rear axle ball joints, check rubber boots			•		•		•		•		•		•		•			AP35.20-P-3552C
☐ Inspect steering and tie rods, inspect rubber boots			•		•		•		•		•		•		•			AP46.00-P-4651C
☐ Inspect suspension struts or shock absorbers and springs																		
Except CODE 487 (Active Body Control)			•		•		•		•		•		•		•			AP32.25-P-3255B
With CODE 487 (Active Body Control)			•		•		•		•		•		•		•			AP32.25-P-3255BS
☐ Inspect driveshaft flexible discs			•		•		•		•		•		•		•			AP41.10-P-4152HA
Check catch, safety catch and hinges on engine hood for proper operation		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Clean visible area of water deflector		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Active Body Control - check fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP32.50-P-3213HA
with CODE 487 (Active Body Control (ABC))																		
Check coolant level and correct if necessary i refer to AH20.00-P-1142-01LFB and AH20.00-P-1142-01MUB i observe correct coolant composition			•		•		•		•		•		•		•			
☐ Check windshield washer system fluid, correct		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8210HA
if necessary	\dashv		_	_	_	_	_	_	_	_	_	-	-	_	_	_		AP42.10-P-4210HA
Check brake fluid level and correct if necessary	-	•	•	•	-	•	-	•	•	•	•	•	•	•	•	•		AP42.00-P-4280HA
Replace brake fluid	-		•		•		•		•		•		•		•			
☐ Check first aid kit		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP68.00-P-6850EW

Required Service Work miles (thousands) Performed years (check if performed)	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80	90	100 10	110 11	120 12	130 13	140 14	150 15	Not OK	
Reset maintenance service indicator in instrument cluster irreminder - if not yet performed		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0043J
Required Additional Work miles (thousands)	2	10	20	30		50	60	70		90	100		120	130	140	150		
Performed years (check if performed)		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK ↓	
Replace main circuit coolant engine 279				•			•			•			•			•		AP20.00-P-2082J
Replace air filter engine 177, 279																		
engine 177				•			•			•			•			•		AP09.10-P-0980K
engine 279				•			•			•			•			•		AP09.10-P-0980SZ
Replace air filter engine 176, 276																		
engine 176						•					•					•		AP09.10-P-0980I
engine 276						•					•					•		AP09.10-P-0980E
Automatic transmission - oil and filter change engine 279 NAG2-VFE+ (transmission 722.9)				•			•			•			•			•		AP27.00-P-2702W
Automatic transmission - oil and filter change transmission 725.09 (AMG)				•			•			•			•			•		AP27.00-P-2702B
Automatic transmission - oil and filter change engine 176, 276																		
transmission 722.9							•						•					AP27.00-P-2702W
transmission 725.0							•						•					AP27.00-P-2702B
☐ Transfer case - Perform oil change transmission 725.09 with CODE M005 (4MATIC)						•					•					•		
☐ Replace spark plugs																		
engine 176, 177						•					•					•		AP15.10-P-1580C
engine 276						•					•					•		AP15.10-P-1580HA
engine 279						•					•					•		AP15.10-P-1580AAA
Replace poly-V-belt engine 176 with CODE 457 (MAGIC BODY CONTROL)							•						•					AR13.21-P-1203MNL
☐ Replace fuel filter													•					AP47.20-P-0780HC
Replace main circuit coolant engine 176, 177, 276													•					AP20.00-P-2082J
observe correct coolant composition																		
Replace low-temperature circuit coolant observe correct coolant compositio																		
engine 176, 177													•					AP20.00-P-2083C
engine 276													•					AP20.00-P-2083I
engine 279													•					AP20.00-P-2083A
Recommended Service miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
Work ☑ Performed years (check if performed)		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK ↓	
☐ Check horn		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Check warning/indicator lamps		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5451HA
Check illumination and interior lighting		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5453HA
Check seatbelts and buckles for proper			•		•		•		•		•		•		•			
operation or damage																		

Recommended Service miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
Work ☑ Performed years		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK	
(check if performed)																	•	
☐ Check windshield wiper, washer and headlamp washer system operation		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8252HA
Replace wiper blades		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof)			•		•		•		•		•		•		•			AP77.20-P-7732HA
Activate Tire Pressure Monitoring System Trefer to vehicle Operator's Manual		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check all exterior lights		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.10-P-8252EW
☐ Check for body paint damage			•		•		•		•		•		•		•			AP60.00-P-0050LF
☐ Check TIREFIT tire sealant expiration date			•	•	•	•	•	•	•	•								AP40.10-P-4054R
(where applicable)		_	_	_	_	_	_	_	_	_	_	_	_	_	_	_		
Check trunk / cargo area light		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		4 D00 40 D 00505M
☐ Check operation of headlamp range adjustment			•		•		•		•		•		•		•			AP82.10-P-8250EW
☐ Check headlamp setting, correct if necessary			•		•		•		•		•		•		•			AP82.10-P-8260HA
☐ Tire rotation (where applicable)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Check thickness of brake pads and discs, front and rear wheels removed																		
Pads		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4252HA
Discs (except CODE B07)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4258HA
Discs (CODE B07)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4258HC
☐ Visually inspect brake system components, hoses, lines and calipers		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
☐ Inspect tires for damage and measure		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.10-P-4051EW
remaining tread life																		
Check chassis and load bearing body components for damage and corrosion			•		•		•		•		•		•		•			
☐ Check ex-factory driving aids With CODE 45P (Disability conversion - Sales control code)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	Ц	AP86.20-P-8649U
Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO) After consultation with customer		•	•	•	•	•												
High Mileage Required Service Work at 1	60,	000	mi	les	or	16 y	yea	rs;	the	n ev	/ery	20,0	000	mile	s or	2 ye	ars	
i Plus any applicable additional work li	ste	d at	the	e er	nd c	of th	ne s	erv	ice	she	eet							
☑ Performed																	Not OK	
(check if performed)																	Ψ	
Reset maintenance service indicator in in	stru	ume	ent d	clus	ter													AP00.20-P-0043J
☐ Replace combination filter																		AP83.00-P-8384HA
☐ Perform brake test																		AP42.00-P-4290BA
☐ Engine – oil and filter change																		
										AP18.00-P-0101MNL								
·										AP18.00-P-0101DD								
engine 276 AP18.00-P-0101CV									AP18.00-P-0101CWZ									
engine 279 AP18.00-P-0101HA								AP18.00-P-0101HA										
☐ Check condition of poly-V-belt																	_	
engine 276, 279																		AP13.22-P-1352EW
engine 176, 177																		AP13.22-P-1352D
☐ Inspect trailer hitch condition and function with CODE 550 (Trailer hitch)	1																	AP31.11-P-3152HA

\square Check thickness of brake pads front and rear	Ш	AP42.10-P-4252HA
☐ Check and correct all tire air pressures, including spare where applicable		AP40.15-P-4061A
☐ Check vehicle underside for leaks and damage		AP00.20-P-0054J
☐ Check all visible engine components for leaks and damage		AP00.20-P-0055A
☐ Inspect front axle and front axle ball joints, check rubber boots		AP33.10-P-3358C
☐ Inspect rear axle and rear axle ball joints, check rubber boots		AP35.20-P-3552C
☐ Inspect steering and tie rods, inspect rubber boots		AP46.00-P-4651C
☐ Inspect suspension struts or shock absorbers and springs		
Except CODE 487 (Active Body Control)		AP32.25-P-3255B
With CODE 487 (Active Body Control)		AP32.25-P-3255BS
☐ Inspect driveshaft flexible discs		AP41.10-P-4152HA
☐ Check catch, safety catch and hinges on engine hood for proper operation		
Clean visible area of water deflector		
Active Body Control - check fluid level and correct if necessary with CODE 487 (Active Body Control (ABC))		AP32.50-P-3213HA
☐ Check coolant level and correct if necessary		
i refer to AH20.00-P-1142-01LFB and AH20.00-P-1142-01MUB		
i observe correct coolant composition		AP82.35-P-8210HA
Check windshield washer system fluid, correct if necessary		AP42.10-P-4210HA
☐ Check brake fluid level and correct if necessary		AP42.00-P-4280HA
Replace brake fluid		
Check first aid kit		AP68.00-P-6850EW
Reset maintenance service indicator in instrument cluster		AP00.20-P-0043J
🗓 reminder - if not yet performed		
i reminder - if not yet performed High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles	es or 2 yea	ars
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 mil Plus any applicable additional work listed at the end of the service sheet Performed	Not Of	
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 mil Plus any applicable additional work listed at the end of the service sheet Performed (check if performed)	Not Oh	
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 mil Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn	Not Oh	ζ
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles. ☐ Plus any applicable additional work listed at the end of the service sheet. ☐ Performed (check if performed). ☐ Check horn. ☐ Check warning/indicator lamps.	Not Or	AP54.30-P-5451HA
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles. ☐ Plus any applicable additional work listed at the end of the service sheet. ☐ Performed (check if performed). ☐ Check horn. ☐ Check warning/indicator lamps. ☐ Check illumination and interior lighting.	Not Or	ζ
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles. ☐ Plus any applicable additional work listed at the end of the service sheet. ☐ Performed (check if performed). ☐ Check horn. ☐ Check warning/indicator lamps.	Not Or	AP54.30-P-5451HA AP54.30-P-5453HA
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles. ☐ Plus any applicable additional work listed at the end of the service sheet. ☐ Performed (check if performed). ☐ Check horn. ☐ Check warning/indicator lamps. ☐ Check illumination and interior lighting.	Not Or	AP54.30-P-5451HA
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles. Plus any applicable additional work listed at the end of the service sheet ☐ Performed (check if performed) ☐ Check horn ☐ Check warning/indicator lamps ☐ Check illumination and interior lighting ☐ Check seatbelts and buckles for proper operation or damage ☐ Check windshield wiper, washer and headlamp washer system operation ☐ Replace wiper blades	Not Or	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles. Plus any applicable additional work listed at the end of the service sheet. Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check seatbelts and buckles for proper operation or damage Check windshield wiper, washer and headlamp washer system operation	Not Or	AP54.30-P-5451HA AP54.30-P-5453HA
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles. Plus any applicable additional work listed at the end of the service sheet ☐ Performed (check if performed) ☐ Check horn ☐ Check warning/indicator lamps ☐ Check illumination and interior lighting ☐ Check seatbelts and buckles for proper operation or damage ☐ Check windshield wiper, washer and headlamp washer system operation ☐ Replace wiper blades ☐ Clean and lubricate panoramic sliding roof guide mechanism	Not Or	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles. Plus any applicable additional work listed at the end of the service sheet. ☑ Performed (check if performed) ☐ Check horn ☐ Check warning/indicator lamps ☐ Check illumination and interior lighting ☐ Check seatbelts and buckles for proper operation or damage ☐ Check windshield wiper, washer and headlamp washer system operation ☐ Replace wiper blades ☐ Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof) ☐ Activate Tire Pressure Monitoring System	Not Or	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 mile Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check seatbelts and buckles for proper operation or damage Check windshield wiper, washer and headlamp washer system operation Replace wiper blades Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof) Activate Tire Pressure Monitoring System refer to vehicle Operator's Manual	Not OF	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA AP77.20-P-7732HA
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles or 16 years; then every 20,00	Not OF	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA AP77.20-P-7732HA
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles in Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check seatbelts and buckles for proper operation or damage Check windshield wiper, washer and headlamp washer system operation Replace wiper blades Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof) Activate Tire Pressure Monitoring System irefer to vehicle Operator's Manual Check all exterior lights Check for body paint damage Check TIREFIT tire sealant expiration date (where applicable)	Not OF	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA AP77.20-P-7732HA AP82.10-P-8252EW AP60.00-P-0050LF
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles. Plus any applicable additional work listed at the end of the service sheet ☐ Performed (check if performed) ☐ Check horn ☐ Check warning/indicator lamps ☐ Check illumination and interior lighting ☐ Check seatbelts and buckles for proper operation or damage ☐ Check windshield wiper, washer and headlamp washer system operation ☐ Replace wiper blades ☐ Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof) ☐ Activate Tire Pressure Monitoring System ☐ refer to vehicle Operator's Manual ☐ Check all exterior lights ☐ Check for body paint damage	Not OF	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA AP77.20-P-7732HA AP82.10-P-8252EW AP60.00-P-0050LF
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles. Plus any applicable additional work listed at the end of the service sheet ☐ Performed (check if performed) ☐ Check horn ☐ Check warning/indicator lamps ☐ Check illumination and interior lighting ☐ Check seatbelts and buckles for proper operation or damage ☐ Check windshield wiper, washer and headlamp washer system operation ☐ Replace wiper blades ☐ Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof) ☐ Activate Tire Pressure Monitoring System ☐ refer to vehicle Operator's Manual ☐ Check all exterior lights ☐ Check for body paint damage ☐ Check TIREFIT tire sealant expiration date (where applicable) ☐ Check operation of headlamp range adjustment	Not OP	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA AP77.20-P-7732HA AP82.10-P-8252EW AP60.00-P-0050LF AP40.10-P-4054R
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 mile Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check seatbelts and buckles for proper operation or damage Check windshield wiper, washer and headlamp washer system operation Replace wiper blades Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof) Activate Tire Pressure Monitoring System refer to vehicle Operator's Manual Check all exterior lights Check for body paint damage Check TIREFIT tire sealant expiration date (where applicable) Check operation of headlamp range adjustment Check headlamp setting, correct if necessary	Not OP	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA AP77.20-P-7732HA AP82.10-P-8252EW AP60.00-P-0050LF AP40.10-P-4054R AP82.10-P-8250EW
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles. Plus any applicable additional work listed at the end of the service sheet ☐ Performed (check if performed) ☐ Check horn ☐ Check warning/indicator lamps ☐ Check illumination and interior lighting ☐ Check seatbelts and buckles for proper operation or damage ☐ Check windshield wiper, washer and headlamp washer system operation ☐ Replace wiper blades ☐ Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof) ☐ Activate Tire Pressure Monitoring System ☐ refer to vehicle Operator's Manual ☐ Check all exterior lights ☐ Check for body paint damage ☐ Check TIREFIT tire sealant expiration date (where applicable) ☐ Check operation of headlamp range adjustment	Not OP	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA AP77.20-P-7732HA AP82.10-P-8252EW AP60.00-P-0050LF AP40.10-P-4054R AP82.10-P-8250EW

Discs (except CODE B07)		AP42.10-P-4258HA
Discs (CODE B07)		AP42.10-P-4258HC
\square Visually inspect brake system components, hoses, lines and calipers		
\square Inspect tires for damage and measure remaining tread life		AP40.10-P-4051EW
\square Check chassis and load bearing body components for damage and corrosion		
☐ Check ex-factory driving aids With CODE 45P (Disability conversion - Sales control code)		AP86.20-P-8649U
Replace battery for KEYLESS-GO key		
with CODE 889 (KEYLESS-GO)		
After consultation with customer After consultation with customer After cons		
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles I Plus any applicable additional work listed at the end of the service sheet	or 2 years	
Prior any applicable additional work listed at the end of the service sheet Performed	Not Ok	(
(check if performed)	•	
☐ Reset maintenance service indicator in instrument cluster		AP00.20-P-0043J
☐ Perform brake test		AP42.00-P-4290BA
☐ Engine – oil and filter change		
engine 176		AP18.00-P-0101MNL
engine 177		AP18.00-P-0101DD
engine 276		AP18.00-P-0101CWZ
engine 279		AP18.00-P-0101HA
☐ Check and correct all tire air pressures, including spare where applicable		AP40.15-P-4061A
Check catch, safety catch and hinges on engine hood for proper operation		
☐ Clean visible area of water deflector		
☐ Active Body Control - check fluid level and correct if necessary with CODE 487 (Active Body Control (ABC))		AP32.50-P-3213HA
☐ Check windshield washer system fluid, correct if necessary		AP82.35-P-8210HA
☐ Check brake fluid level and correct if necessary		AP42.10-P-4210HA
☐ Check first aid kit		AP68.00-P-6850EW
Reset maintenance service indicator in instrument cluster I reminder - if not yet performed		AP00.20-P-0043J
High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000	miles or 2 vea	nrs
Plus any applicable additional work listed at the end of the service sheet		
☑ Performed	Not Ok	(
(check if performed)	•	
□ Check horn		
☐ Check warning/indicator lamps		AP54.30-P-5451HA
☐ Check illumination and interior lighting		AP54.30-P-5453HA
\square Check windshield wiper, washer and headlamp washer system operation		AP82.35-P-8252HA
Replace wiper blades		
☐ Activate Tire Pressure Monitoring System ☐ refer to vehicle Operator's Manual		
☐ Check all exterior lights		AP82.10-P-8252EW
\square Check TIREFIT tire sealant expiration date (where applicable)		AP40.10-P-4054R
☐ Check trunk / cargo area light		
☐Tire rotation (where applicable)		
\square Check thickness of brake pads and discs, front and rear wheels removed		
Pads		AP42.10-P-4252HA
Discs (except CODE B07)		AP42.10-P-4258HA

Discs (CODE B07)		AP42.10-P-4258HC
☐ Visually inspect brake system components,	hoses, lines and calipers	
☐ Inspect tires for damage and measure remains	·	AP40.10-P-4051EW
☐ Check ex-factory driving aids		AP86.20-P-8649U
With CODE 45P (Disability conversion - Sal	les control code)	
Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO)		
After consultation with customer		
High Mileage Additional Work Performed (check if performed)		
Replace main circuit coolant engine 279	If more than 30,000 miles or 3 years since last replacement	AP20.00-P-2082J
Replace air filter engine 177, 279		
engine 177	If more than 30,000 miles or 3 years since last replacement	AP09.10-P-0980K
engine 279	If more than 30,000 miles or 3 years since last replacement	 AP09.10-P-0980SZ
Replace air filter engine 176, 276		
engine 176	If more than 50,000 miles or 5 years since last replacement	AP09.10-P-0980I
engine 276	If more than 50,000 miles or 5 years since last replacement	 AP09.10-P-0980E
Automatic transmission - oil and filter change engine 279 NAG2-VFE+ (transmission 722.9)	If more than 30,000 miles or 3 years since last replacement	AP27.00-P-2702W
Automatic transmission - oil and filter change transmission 725.09 (AMG)	If more than 30,000 miles or 3 years since last replacement	AP27.00-P-2702B
Automatic transmission - oil and filter change engine 176, 276		
transmission 722.9	If more than 60,000 miles or 6 years since last replacement	AP27.00-P-2702W
transmission 725.0	If more than 60,000 miles or 6 years since last replacement	 AP27.00-P-2702B
Transfer case - Perform oil change transmission 725.09 with CODE M005 (4MATIC)	If more than 50,000 miles or 5 years since last replacement	
Replace spark plugs		
engine 176, 177	If more than 50,000 miles or 5 years since last replacement	AP15.10-P-1580C
engine 276	If more than 50,000 miles or 5 years since last replacement	AP15.10-P-1580HA
engine 279	If more than 50,000 miles or 5 years since last replacement	AP15.10-P-1580AAA
Replace poly-V-belt engine 176 with CODE 457 (MAGIC BODY CONTROL)	If more than 60,000 miles or 6 years since last replacement	AR13.21-P-1203MNL
Replace fuel filter	If more than 120,000 miles or 12 years since last replacement	AP47.20-P-0780HC
Replace main circuit coolant engine 176, 177, 276	If more than 120,000 miles or 12 years since last replacement	AP20.00-P-2082J
i observe correct coolant composition		
Replace low-temperature circuit coolant		
i observe correct coolant compositio		
engine 176, 177	If more than 120,000 miles or 12 years since last replacement	AP20.00-P-2083C
engine 276	If more than 120,000 miles or 12 years since last replacement	AP20.00-P-2083I
engine 279	If more than 120,000 miles or 12 years since last replacement	AP20.00-P-2083A

Tire inflation pressure (bar/psi)													
LF	RF	LR	RR	Spare									

Tire tread depth (mm)												
	LF	RF	LR	RR								
outside												
center												
inside												