

Mercedes-Benz

AP00.20-U-1208IN

SERVICE SHEET for Mercedes-Benz Maintenance System (USA)

Model Year 201	8	Мос	del 222		
Customer:			Repair order nur	nber:	
Tire Rotation (non-staggered width wheel setup only)	A 5,000-mile recommende likely necessitate tire rotati each 10,000-mile maintena 10,000-mile maintenance s	on at least once in between ance service and at every	Tires rotated	YES	NO
Note: For any contract the cause and perfore	ondition found while performi m the repair using a separat	ing the checks or inspections e repair order.	s included in this m	naintenance sheet	, determine
Current mileage read	ling:	0	il grade/viscosity:_		
Additional notes:					
Service work to be poservice advisor:	erformed as advised by	Completion date:	Confirm work has below:	been performed l	oy signing

Mercedes-Benz USA, LLC Reproduction or translation in whole or in part is not permitted without written authorization from the publisher. 1-800-FOR-MERCedes

Required Service Work miles (thousands) Performed years (check if performed)	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90 9	100 10	110 11	120 12	130 13	140 14	150 15	Not OK	
Reset maintenance service indicator in in instrument cluster		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0043J
Replace combination filter			•		•		•		•		•		•		•			AP83.00-P-8384HA
Perform brake test		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.00-P-4290BA
□ Engine – oil and filter change engine 176		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101MNL
engine 177		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101DD
engine 276		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101CWZ
engine 279		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP18.00-P-0101HA
Check condition of poly-V-belt engine 276, 279			•		•		•		•		•		•		•			AP13.22-P-1352EW
engine 176, 177			٠		٠		•		•		•		•		•			AP13.22-P-1352D
□ Inspect trailer hitch condition and function with CODE 550 (Trailer hitch)			•		•		•		•		•		•		•			AP31.11-P-3152HA
\Box Check thickness of brake pads front and rear			•		٠		•		•		٠		•		•			AP42.10-P-4252HA
□ Check and correct all tire air pressures, including spare where applicable		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP40.15-P-4061A
\Box Check vehicle underside for leaks and damage			•		٠		•		•		٠		•		٠			AP00.20-P-0054J
Check all visible engine components for leaks and damage			•		•		•		•		•		•		•			AP00.20-P-0055A
\Box Inspect front axle and front axle ball joints, check rubber boots			•		•		•		•		•		•		•			AP33.10-P-3358C
□ Inspect rear axle and rear axle ball joints, check rubber boots			•		•		•		•		•		•		•			AP35.20-P-3552C
□ Inspect steering and tie rods, inspect rubber boots			•		•		•		•		•		•		•			AP46.00-P-4651C
\Box Inspect suspension struts or shock absorbers and springs																	_	
Except CODE 487 (Active Body Control)			•		٠		•		•		•		•		•			AP32.25-P-3255B
With CODE 487 (Active Body Control)			٠		٠		٠		٠		٠		٠		٠			AP32.25-P-3255BS
□ Inspect driveshaft flexible discs			٠		٠		•		•		٠		•		•			AP41.10-P-4152HA
Check catch, safety catch and hinges on engine hood for proper operation		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
□ Clean visible area of water deflector		٠	•	•	٠	•	•	٠	•	•	٠	•	•	•	•	•		
□ Active Body Control - check fluid level and correct if necessary with CODE 487 (Active Body Control (ABC))		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP32.50-P-3213HA
Check coolant level and correct if necessary refer to AH20.00-P-1142-01LFB and AH20.00-P-1142-01MUB observe correct coolant composition			•		•		•		•		•		•		•			
Check windshield washer system fluid, correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP82.35-P-8210HA
Check brake fluid level and correct if necessary		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP42.10-P-4210HA
□ Replace brake fluid			•		•		•		•		٠		٠		٠			AP42.00-P-4280HA
Check first aid kit		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP68.00-P-6850EW

Required Service Workmiles (thousands)Performedyears(check if performed)	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90 9	100 10	110 11	120 12	130 13	140 14	150 15	Not OK ✔	
Reset maintenance service indicator in instrument cluster		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP00.20-P-0043J
Required Additional Workmiles (thousands)Performedyears(check if performed)	2	10 1	20 2	30 3	40 4	50 5	60 6	70 7	80 8	90 9	100 10	110 11	120 12	130 13	140 14	150 15	Not OK	
Replace main circuit coolant engine 279				•			•			•			•			•		AP20.00-P-2082J
Replace air filter engine 177, 279 engine 177				•			•			•			•			•		AP09.10-P-0980K
engine 279				•			•			•			•			•		AP09.10-P-0980SZ
Replace air filter engine 176, 276 engine 176 engine 276 Automatic transmission - oil and filter change				•		•	•			•	•		•			•		AP09.10-P-0980I AP09.10-P-0980E AP27.00-P-2702W
engine 279 NAG2-VFE+ (transmission 722.9)				-			-			-			-			-		
Automatic transmission - oil and filter change transmission 725.09 (AMG)				•			•			•			•			•		AP27.00-P-2702B
Automatic transmission - oil and filter change engine 176, 276 transmission 722.9 transmission 725.0							•						•					AP27.00-P-2702W AP27.00-P-2702B
□ Transfer case - Perform oil change transmission 725.09 with CODE M005 (4MATIC)						•					•					•		
□ Replace spark plugs engine 176, 177 engine 276						•					•					•••		AP15.10-P-1580C AP15.10-P-1580HA
engine 279						•					•					•		AP15.10-P-1580AAA
Replace poly-V-belt engine 176 with CODE 457 (MAGIC BODY CONTROL)							•						•					AR13.21-P-1203MNL
Replace fuel filter													•					AP47.20-P-0780HC
□ Replace main circuit coolant engine 176, 177, 276													•					AP20.00-P-2082J
Replace low-temperature circuit coolant boserve correct coolant compositio engine 176, 177 engine 276 engine 279													•					AP20.00-P-2083C AP20.00-P-2083I AP20.00-P-2083A
Recommended Service miles (thousands)	2	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150		
Work Image (areadinable) Image (areadinable) Work Image (areadinable) (check if performed)		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	Not OK ↓	
Check horn		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Check warning/indicator lamps		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		AP54.30-P-5451HA
Check illumination and interior lighting		•	•	•	•	•	•	•	•	•	•	•	•	٠	•	٠		AP54.30-P-5453HA
Check seatbelts and buckles for proper operation or damage			•		•		•		•		•		•		•			

	AP82.35-P-8252HA AP77.20-P-7732HA AP77.20-P-7732HA AP82.10-P-8252EW AP60.00-P-0050LF AP40.10-P-4054R AP82.10-P-8250EW AP82.10-P-8250EW AP82.10-P-8250HA AP42.10-P-4252HA AP42.10-P-4258HA AP42.10-P-4258HC
	AP82.35-P-8252HA AP77.20-P-7732HA AP77.20-P-7732HA AP82.10-P-8252EW AP60.00-P-0050LF AP40.10-P-4054R AP82.10-P-8250EW AP82.10-P-8250EW AP82.10-P-8250EW
	AP77.20-P-7732HA AP82.10-P-8252EW AP60.00-P-0050LF AP40.10-P-4054R AP82.10-P-8250EW AP82.10-P-8260HA AP82.10-P-8260HA AP42.10-P-4252HA AP42.10-P-4258HA
	AP77.20-P-7732HA AP82.10-P-8252EW AP60.00-P-0050LF AP40.10-P-4054R AP82.10-P-8250EW AP82.10-P-8260HA AP82.10-P-8260HA AP42.10-P-4252HA AP42.10-P-4258HA
	AP82.10-P-8252EW AP60.00-P-0050LF AP40.10-P-4054R AP82.10-P-8250EW AP82.10-P-8260HA AP42.10-P-4252HA AP42.10-P-4258HA
	AP82.10-P-8252EW AP60.00-P-0050LF AP40.10-P-4054R AP82.10-P-8250EW AP82.10-P-8260HA AP42.10-P-4252HA AP42.10-P-4258HA
	AP60.00-P-0050LF AP40.10-P-4054R AP82.10-P-8250EW AP82.10-P-8260HA AP42.10-P-4252HA AP42.10-P-4258HA
	AP60.00-P-0050LF AP40.10-P-4054R AP82.10-P-8250EW AP82.10-P-8260HA AP42.10-P-4252HA AP42.10-P-4258HA
	AP40.10-P-4054R AP82.10-P-8250EW AP82.10-P-8260HA AP42.10-P-4252HA AP42.10-P-4258HA
	AP82.10-P-8250EW AP82.10-P-8260HA AP42.10-P-4252HA AP42.10-P-4258HA
	AP82.10-P-8260HA AP42.10-P-4252HA AP42.10-P-4258HA
	AP82.10-P-8260HA AP42.10-P-4252HA AP42.10-P-4258HA
	AP42.10-P-4252HA AP42.10-P-4258HA
	AP42.10-P-4258HA
	AP42.10-P-4258HA
	AP42.10-P-4258HA
	ΔP42 10-P-4258UC
	11 TZ. 10-F-420000
	AP40.10-P-4051EW
	AP86.20-P-8649U
ears	
	•
•	AP00.20-P-0043J
	AP83.00-P-8384HA
	AP42.00-P-4290BA
	AP18.00-P-0101MNL
	AP18.00-P-0101DD AP18.00-P-0101CWZ
	AP18.00-P-0101CWZ
	AP13.22-P-1352EW
	AP13.22-P-1352D
	AP31.11-P-3152HA
	Pars Not OK ↓

Check thickness of brake pads front and rear		AP42.10-P-4252HA
Check and correct all tire air pressures, including spare where applicable		AP40.15-P-4061A
Check vehicle underside for leaks and damage		AP00.20-P-0054J
Check all visible engine components for leaks and damage		AP00.20-P-0055A
□ Inspect front axle and front axle ball joints, check rubber boots		AP33.10-P-3358C
□ Inspect rear axle and rear axle ball joints, check rubber boots		AP35.20-P-3552C
□ Inspect steering and tie rods, inspect rubber boots		AP46.00-P-4651C
□ Inspect suspension struts or shock absorbers and springs		
Except CODE 487 (Active Body Control)		AP32.25-P-3255B
With CODE 487 (Active Body Control)		AP32.25-P-3255BS
Inspect driveshaft flexible discs		AP41.10-P-4152HA
Check catch, safety catch and hinges on engine hood for proper operation		
Clean visible area of water deflector		
Active Body Control - check fluid level and correct if necessary with CODE 487 (Active Body Control (ABC))		AP32.50-P-3213HA
Check coolant level and correct if necessary		
irefer to AH20.00-P-1142-01LFB and AH20.00-P-1142-01MUB		
Observe correct coolant composition		AP82.35-P-8210HA
Check windshield washer system fluid, correct if necessary		AP42.10-P-4210HA
Check brake fluid level and correct if necessary		
C Replace brake fluid		AP42.00-P-4280HA
Check first aid kit		AP68.00-P-6850EW
Reset maintenance service indicator in instrument cluster		AP00.20-P-0043J
I have in allow the produced the second		
I reminder - if not yet performed	les or 2 vez	are
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 mi	les or 2 yea	ars
	les or 2 yea Not Of	
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 mi	Not Of ↓	
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000	Not Of	
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed)	Not Of ↓	
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn	Not Of	۲
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps	Not Of	(AP54.30-P-5451HA
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles I Plus any applicable additional work listed at the end of the service sheet ⊠ Performed (check if performed) □ Check horn □ Check warning/indicator lamps □ Check illumination and interior lighting	Not Of	(AP54.30-P-5451HA
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check seatbelts and buckles for proper operation or damage	Not Of	(AP54.30-P-5451HA AP54.30-P-5453HA
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles I Plus any applicable additional work listed at the end of the service sheet ⊠ Performed (check if performed) □ Check horn □ Check warning/indicator lamps □ Check illumination and interior lighting □ Check seatbelts and buckles for proper operation or damage □ Check windshield wiper, washer and headlamp washer system operation	Not Of	(AP54.30-P-5451HA AP54.30-P-5453HA
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles Image: Performed (check if performed) Image: Check horn Image: Check warning/indicator lamps Image: Check warning/indicator lamps Image: Check seatbelts and buckles for proper operation or damage Image: Check windshield wiper, washer and headlamp washer system operation Image: Replace wiper blades Image: Check and lubricate panoramic sliding roof guide mechanism	Not Of	AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles Image: Performed (check if performed) □ Check horn □ Check warning/indicator lamps □ Check illumination and interior lighting □ Check seatbelts and buckles for proper operation or damage □ Check windshield wiper, washer and headlamp washer system operation □ Replace wiper blades □ Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof)	Not OF	AP54.30-P-5451HA AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA AP77.20-P-7732HA
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles Image: Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check seatbelts and buckles for proper operation or damage Check windshield wiper, washer and headlamp washer system operation Replace wiper blades Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof) Activate Tire Pressure Monitoring System	Not Of	AP54.30-P-5451HA AP54.30-P-5453HA AP54.30-P-5453HA AP82.35-P-8252HA AP77.20-P-7732HA AP77.20-P-7732HA
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles Image: Performed (check if performed) Image: Check horn Image: Check warning/indicator lamps Image: Check warning/indicator lamps Image: Check seatbelts and buckles for proper operation or damage Image: Check windshield wiper, washer and headlamp washer system operation Image: Replace wiper blades Image: Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof) Image: Activate Tire Pressure Monitoring System Image: Replace wiper to vehicle Operator's Manual		 AP54.30-P-5451HA AP54.30-P-5453HA AP54.30-P-5453HA AP82.35-P-8252HA AP77.20-P-7732HA AP82.10-P-8252EW AP60.00-P-0050LF
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles Image: Performed service additional work listed at the end of the service sheet Image: Performed service sheet service service sheet service service sheet service sheet service service service sheet service	Not OP	AP54.30-P-5451HA AP54.30-P-5453HA AP54.30-P-5453HA AP82.35-P-8252HA AP77.20-P-7732HA AP77.20-P-7732HA
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 mility Image: Plus any applicable additional work listed at the end of the service sheet Image: Performed (check if performed) Image: Check horn Image: Check warning/indicator lamps	Not OP	AP54.30-P-5451HA AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA AP82.35-P-8252EW AP82.10-P-8252EW AP60.00-P-0050LF AP40.10-P-4054R
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles I Plus any applicable additional work listed at the end of the service sheet ⊠ Performed (check if performed) □ Check horn □ Check warning/indicator lamps □ Check seatbelts and buckles for proper operation or damage □ Check windshield wiper, washer and headlamp washer system operation □ Replace wiper blades □ Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof) □ Activate Tire Pressure Monitoring System I refer to vehicle Operator's Manual □ Check for body paint damage □ Check TIREFIT tire sealant expiration date (where applicable)	Not OP	 AP54.30-P-5451HA AP54.30-P-5453HA AP54.30-P-5453HA AP82.35-P-8252HA AP77.20-P-7732HA AP82.10-P-8252EW AP60.00-P-0050LF
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check seatbelts and buckles for proper operation or damage Check windshield wiper, washer and headlamp washer system operation Replace wiper blades Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof) Activate Tire Pressure Monitoring System I refer to vehicle Operator's Manual Check all exterior lights Check for body paint damage Check trunk / cargo area light	Not OP	AP54.30-P-5451HA AP54.30-P-5451HA AP54.30-P-5453HA AP82.35-P-8252HA AP82.35-P-8252EW AP82.10-P-8252EW AP60.00-P-0050LF AP40.10-P-4054R
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 mile I Plus any applicable additional work listed at the end of the service sheet Performed (check if performed) Check horn Check warning/indicator lamps Check illumination and interior lighting Check seatbelts and buckles for proper operation or damage Check windshield wiper, washer and headlamp washer system operation Replace wiper blades Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof) Activate Tire Pressure Monitoring System I refer to vehicle Operator's Manual Check for body paint damage Check for body paint damage Check trunk / cargo area light Check operation of headlamp range adjustment	Not OP	AP54.30-P-5451HA AP54.30-P-5453HA AP54.30-P-5453HA AP82.35-P-8252HA AP82.35-P-8252HA AP77.20-P-7732HA AP60.00-P-0750LF AP40.10-P-8252EW AP60.00-P-0050LF AP40.10-P-4054R
High Mileage Recommended Service Work at 160,000 miles or 16 years; then every 20,000 miles Image: Performed (check if performed) Check horn Check horn Check warning/indicator lamps Check illumination and interior lighting Check seatbelts and buckles for proper operation or damage Check windshield wiper, washer and headlamp washer system operation Replace wiper blades Clean and lubricate panoramic sliding roof guide mechanism with CODE 413 (Panoramic sliding sunroof) Activate Tire Pressure Monitoring System Image: refer to vehicle Operator's Manual Check for body paint damage Check trunk / cargo area light Check to peration of headlamp range adjustment Check headlamp setting, correct if necessary	Not OP	AP54.30-P-5451HA AP54.30-P-5453HA AP54.30-P-5453HA AP82.35-P-8252HA AP82.35-P-8252HA AP77.20-P-7732HA AP60.00-P-0750LF AP40.10-P-8252EW AP60.00-P-0050LF AP40.10-P-4054R

Discs (except CODE B07)		AP42.10-P-4258HA
Discs (CODE B07)		AP42.10-P-4258HC
□ Visually inspect brake system components, hoses, lines and calipers		
□ Inspect tires for damage and measure remaining tread life		AP40.10-P-4051EW
Check chassis and load bearing body components for damage and corrosion		
Check ex-factory driving aids With CODE 45P (Disability conversion - Sales control code)		AP86.20-P-8649U
Replace battery for KEYLESS-GO key		
with CODE 889 (KEYLESS-GO) After consultation with customer		
High Mileage Required Service Work at 170,000 miles or 17 years; then every 20,000 miles or		
I Plus any applicable additional work listed at the end of the service sheet	n z years	
Performed	Not Of	(
(check if performed)	$\mathbf{+}$	
Reset maintenance service indicator in instrument cluster		AP00.20-P-0043J
Perform brake test		AP42.00-P-4290BA
Engine – oil and filter change		
engine 176		AP18.00-P-0101MNL
engine 177		AP18.00-P-0101DD
engine 276		AP18.00-P-0101CWZ
engine 279		AP18.00-P-0101HA
Check and correct all tire air pressures, including spare where applicable		AP40.15-P-4061A
Check catch, safety catch and hinges on engine hood for proper operation		
Clean visible area of water deflector		
Active Body Control - check fluid level and correct if necessary with CODE 487 (Active Body Control (ABC))		AP32.50-P-3213HA
Check windshield washer system fluid, correct if necessary		AP82.35-P-8210HA
Check brake fluid level and correct if necessary		AP42.10-P-4210HA
Check first aid kit		AP68.00-P-6850EW
 Reset maintenance service indicator in instrument cluster I reminder - if not yet performed 		AP00.20-P-0043J
High Mileage Recommended Service Work at 170,000 miles or 17 years; then every 20,000 r	niles or 2 yea	ars
I Plus any applicable additional work listed at the end of the service sheet	•	
Performed	Not Of	K
(check if performed)	<u> </u>	
Check horn		
Check warning/indicator lamps		AP54.30-P-5451HA
Check illumination and interior lighting		AP54.30-P-5453HA
Check windshield wiper, washer and headlamp washer system operation		AP82.35-P-8252HA
Replace wiper blades		
Activate Tire Pressure Monitoring System I refer to vehicle Operator's Manual		
Check all exterior lights		AP82.10-P-8252EW
Check TIREFIT tire sealant expiration date (where applicable)		AP40.10-P-4054R
Check trunk / cargo area light		
□ Tire rotation (where applicable)		
Check thickness of brake pads and discs, front and rear wheels removed		
Pads		AP42.10-P-4252HA
Discs (except CODE B07)		AP42.10-P-4258HA

Discs (CODE B07)		AP42.10-P-4258HC
□ Visually inspect brake system components,	hoses lines and caliners	
□ Inspect tires for damage and measure remain	· · ·	AP40.10-P-4051EW
Check ex-factory driving aids		AP86.20-P-8649U
With CODE 45P (Disability conversion - Sal	les control code)	
Replace battery for KEYLESS-GO key with CODE 889 (KEYLESS-GO)		
After consultation with customer		
High Mileage Additional Work Performed (check if performed)		
Replace main circuit coolant engine 279	If more than 30,000 miles or 3 years since last replacement	AP20.00-P-2082J
Replace air filter engine 177, 279		
engine 177	If more than 30,000 miles or 3 years since last replacement	AP09.10-P-0980K
engine 279	If more than 30,000 miles or 3 years since last replacement	AP09.10-P-0980SZ
Replace air filter engine 176, 276		
engine 176	If more than 50,000 miles or 5 years since last replacement	AP09.10-P-0980I
engine 276	If more than 50,000 miles or 5 years since last replacement	AP09.10-P-0980E
Automatic transmission - oil and filter change engine 279 NAG2-VFE+ (transmission 722.9)	If more than 30,000 miles or 3 years since last replacement	AP27.00-P-2702W
Automatic transmission - oil and filter change transmission 725.09 (AMG)	If more than 30,000 miles or 3 years since last replacement	AP27.00-P-2702B
Automatic transmission - oil and filter change engine 176, 276		
transmission 722.9	If more than 60,000 miles or 6 years since last replacement	AP27.00-P-2702W
transmission 725.0	If more than 60,000 miles or 6 years since last replacement	AP27.00-P-2702B
Transfer case - Perform oil change transmission 725.09 with CODE M005 (4MATIC)	If more than 50,000 miles or 5 years since last replacement	
Replace spark plugs		
engine 176, 177	If more than 50,000 miles or 5 years since last replacement	AP15.10-P-1580C
engine 276	If more than 50,000 miles or 5 years since last replacement	AP15.10-P-1580HA
engine 279	If more than 50,000 miles or 5 years since last replacement	 AP15.10-P-1580AAA
Replace poly-V-belt engine 176 with CODE 457 (MAGIC BODY CONTROL)	If more than 60,000 miles or 6 years since last replacement	AR13.21-P-1203MNL
Replace fuel filter	If more than 120,000 miles or 12 years since last replacement	AP47.20-P-0780HC
Replace main circuit coolant engine 176, 177, 276	If more than 120,000 miles or 12 years since last replacement	AP20.00-P-2082J
i observe correct coolant composition		
Replace low-temperature circuit coolant		
i observe correct coolant compositio		
engine 176, 177	If more than 120,000 miles or 12 years since last replacement	AP20.00-P-2083C
engine 276	If more than 120,000 miles or 12 years since last replacement	AP20.00-P-2083I
engine 279	If more than 120,000 miles or 12 years since last replacement	 AP20.00-P-2083A

Tire infl	ation pre	ssure (b	oar/psi)	
LF	RF	LR	RR	Spare

Tire trea	nd dept	th (mm)		
	LF	RF	LR	RR
outside				
center				
inside				