NTF 715 Nitrogen Tire Filling System BOSCH NTF 715

The technician's choice for versatility, ease of use and efficiency.

NTF 715 Nitrogen Tire Filling System

Properly inflated tires increase fuel efficiency, improve vehicle handling and prolong tire life. The portable, fully-automatic Bosch NTF 715 offers today's technicians the quality and performance they expect from the Bosch brand at a competitive price. Feature-for-feature it's the best way to get in on this new and fast-growing segment of the auto service industry.

Quad Filtration System



- 1 H₂O separator 99.9% efficiency
- 2 Oil separator 99.9% efficiency
- 3 Carbon filter bed separates and purges random gases
- Fine particulate filter traps fine particulates and residual moisture



Foam-filled rear wheels maintain shape and won't go flat.



Convenient side mount hose storage.



Specifications

Air Supply	100 to 150 psi (6.9 to 10.	100 to 150 psi (6.9 to 10.3 bar) required	
Electrical	Standard 110V for ba	attery recharge	
Shipping dimer		1 x 25"W x 26"D 3.5cm x 66cm)	
Weight	Approximately	195 lbs (88 kg)	
Controls	2 ball valves plus digital	2 ball valves plus digital tire fill controls	
Vacuum	Venturi generato	r (17 InHg max)	
Service time/vehicle 7 minutes average (average tire size for data: 225/60/R15)			
Tires per hour (nax. incl. tank refill)	47 tires	
Storage tank ca	pacity	15 gal (56.8 ltr)	
Nitrogen purity	level 95% or	98% (at outlet)	
Hose		green air hose 18 ft (5.5m) working length 1/4" air hose 24 ft (7.3m); Two 12 ft (3.7m)	
Warranty		nbrane: 5 years nent P/L: 1 year	

We reserve the right to modify technical specifications and equipment.

Optional Accessories


F00E900179 Wireless remote technician notification system

Essential Features

- Automatic operation inflates up to six tires simultaneously.
- Battery powered fill controller makes this unit totally portable.
- ► The technician can easily select two choices of N₂ purity.
- Advanced 5.1 CFM large-bore membrane for enhanced nitrogen purity and performance.
- Superb filtration system promotes purity and membrane longevity.
- Easy rolling foam-filled rear wheels won't go flat.
- Vacuum system removes more residual air than traditional systems.
- Auto shut-off minimizes compressor use for energy savings.
- On-board tank conveniently stores generated nitrogen.
- Quickly and simultaneously deflates four tires to atmospheric pressure.
- Two service counters one records full service and one for top-offs.



Rechargeable battery provides power for a full day of use.



 N_2 purity selector is simple to use and maximizes market adaptability.



Fill gun features illuminated digital display, superb accuracy, and durable rubber-coated housing.